


LAMP PART NO.	COLOR GREEN	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS) (AVG.)
BF20100-11B	x = 0.318±0.03 y = 0.556±0.03	780 @ 0°C	260	5	40,000 REF.	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		COMPONENTS CORPORATION				
			DRAWN BY L. WENGSTROM		APPV'D BY DATE J.K. 3/15/04		SIZE A	FSCM NO. 55335	DRAWING NO. BF20100-11B		
A DIMENSION CHANGES RELEASE			3/15/04 3/10/04		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE	RELEASED DATE 3/10/04	REVISION DATE 3/15/04	REV. NO. A	SHEET 1 OF 1
REV. NO.	DESCRIPTION/ECO NUMBER		APPV'D DATE								