

Part: 0259.750  
 Series: 259 Series - Hazardous Area Safe-T-Plus Fuse  
 Technology: Electronic Special Purpose

PARAMETERS		
Package Type	Pkg Type	Radial Leaded
Mount Method	Mount	Through Hole
		0.0000
Current Rating	Amp Rating (A)	0.7500
Fuse Class	Class	Supplemental
Peak Pulse Current - 10x1000	I <sub>PP</sub> 10x1000	0.0000
Peak Pulse Current - 10x560	I <sub>PP</sub> 10x560	0.0000
Peak Pulse Current - 2x10	I <sub>PP</sub> 2x10	0.0000
Peak Pulse Current - 10x160	I <sub>PP</sub> 10x160	0.0000
Marking Code	Marking	
Mounting Method - Second selection	Mounting Method 2	
Fuse Opening Characteristic	Opening Char	Fast-Acting
Operational Use	OpUse	One-Time
Lead-Free	Pb Free	N
Cap Plating	Plating	
Package Size/Form Factor	Size	Other
Voltage Drop	Voltage Drop (mV)	0.2300
Voltage Rating	Voltage Rating (V)	125
Nominal Resistance (Ohms)	Resistance (Ohms)	0.1900
Norminal Melting I <sup>2</sup> t	I <sup>2</sup> t (A <sup>2</sup> Sec)	0.062000 Interrupt Ratings 50A @ 125V 300A @ 125V



**PROTECTS AGAINST:**

**Other Threats**

Short Circuit/Current Overload