

DC Fan

- AD 15mm ~ 172mm / Thickness : min 04mm ~ max 51mm
- AS 40mm ~ 140mm / Thickness : min 28mm ~ max 51mm
- AG 20mm ~ 127mm / Thickness : min 10mm ~ max 38mm

Bearing type: ◎=Ball ※=Sleeve ●=Hypro Bearing

	Frame size (mm)	Model No.	Bearing Type	Rated Voltage (VDC)	Current (A)	Power (W)	Rated Speed (RPM)	Maximum AirFlow (CMM) (CFM)	Maximum Pressure (InAq) (mmAq)	*Noise Level (dB/A)	Weight (g)
AG4015	40x40x15	AG04012LB157300	◎	12	0.07	0.84	7000	0.26 9.36	0.22 5.69	33.2	21
	40x40x15	AG04012MB157300	◎	12	0.09	1.08	8000	0.30 10.56	0.29 7.29	36.9	21
	40x40x15	AG04012HB157300	◎	12	0.12	1.44	9000	0.34 11.99	0.35 8.94	39.6	21
	40x40x15	AG04012UB157300	◎	12	0.17	2.04	10000	0.38 13.31	0.42 10.69	41.7	21
	40x40x15	AG04012XB157300	◎	12	0.21	2.52	11000	0.42 14.69	0.52 13.09	43.5	21
AD4020	40x40x20	AD0405DB-C50(T1)	◎※●	5	0.09	0.45	4200	0.13 4.49	0.08 2.03	17.5	28
	40x40x20	AD0405LB-C50(T1)	◎※●	5	0.14	0.70	6200	0.20 7.00	0.17 4.19	30.0	28
	40x40x20	AD0405MB-C50(T1)	◎※●	5	0.16	0.80	6900	0.22 7.74	0.20 5.08	33.0	28
	40x40x20	AD0405HB-C50(T1)	◎※●	5	0.25	1.25	7800	0.25 8.80	0.28 7.11	36.0	28
	40x40x20	AD0412DB-C50(T1)	◎※●	12	0.04	0.48	4200	0.13 4.49	0.08 2.03	17.5	28
	40x40x20	AD0412LB-C50(T1)	◎※●	12	0.07	0.84	6200	0.20 7.00	0.17 4.19	30.0	28
	40x40x20	AD0412MB-C50(T1)	◎※●	12	0.08	0.96	6900	0.22 7.74	0.20 5.08	33.0	28
	40x40x20	AD0412HB-C50(T1)	◎※●	12	0.10	1.20	7800	0.25 8.80	0.28 7.11	36.0	28
	40x40x20	AD0412UB-C50(T1)	◎※●	12	0.14	1.68	8500	0.27 9.58	0.32 8.13	37.5	28
	40x40x20	AD0424DB-C50(T1)	◎※●	24	0.14	1.68	4200	0.13 4.49	0.08 2.03	17.5	28
	40x40x20	AD0424LB-C50(T1)	◎※●	24	0.05	1.20	6200	0.20 7.00	0.17 4.19	30.0	28
	40x40x20	AD0424MB-C50(T1)	◎※●	24	0.06	1.44	6900	0.22 7.74	0.20 5.08	33.0	28
	40x40x20	AD0424HB-C50(T1)	◎※●	24	0.07	1.68	7800	0.25 8.80	0.28 7.11	36.0	28
	AG4020	40x40x20	AG04012XB205100	◎	12	0.11	1.32	8500	0.31 11.00	0.28 7.01	35.0
40x40x20		AG04012VB205100	◎	12	0.22	2.64	10000	0.43 15.10	0.45 11.43	39.4	28
AD4020GP	40x40x20	AD0412LB-C73GP(P)	◎	12	0.08	0.96	5000	0.18 6.40	0.15 3.81	19.0	28
	40x40x20	AD0412MB-C73GP(P)	◎	12	0.12	1.44	6200	0.23 8.00	0.23 5.84	26.0	28
	40x40x20	AD0412HB-C73GP(P)	◎	12	0.14	1.68	7200	0.27 9.40	0.32 8.13	30.0	28
	40x40x20	AD0412UB-C73GP(P)	◎	12	0.15	1.80	8200	0.31 11.00	0.40 10.16	33.0	28
	40x40x20	AD0412XB-C73GP(P)	◎	12	0.24	2.88	10000	0.37 13.00	0.54 13.72	42.0	28
AD4028	40x40x28	AD0412DB-B31	◎	12	0.05	0.60	4500	0.17 5.90	0.09 2.34	19.2	38
	40x40x28	AD0412LB-B31	◎	12	0.08	0.96	6000	0.22 7.70	0.17 4.32	32.0	38
	40x40x28	AD0412MB-B31	◎	12	0.10	1.20	7500	0.27 9.60	0.22 5.59	34.6	38
	40x40x28	AD0412HB-B31	◎	12	0.16	1.92	9000	0.35 12.20	0.35 8.76	39.0	38
	40x40x28	AD0412UB-B31	◎	12	0.20	2.40	10000	0.37 13.10	0.45 11.43	42.5	38
AS4028	40x40x28	AD0424HB-B31	◎	24	0.08	1.92	8100	0.31 10.80	0.27 6.96	36.2	38
	40x40x28	AS04012DB2856A0(00LAP)	◎	12	0.15	1.80	10000	0.31 10.95	0.69 17.63	40.3	41
	40x40x28	AS04012LB2856A0(00LAP)	◎	12	0.16	1.92	11000	0.34 12.08	0.85 21.64	43.9	41
	40x40x28	AS04012MB2856A0(00LAP)	◎	12	0.20	2.40	12000	0.38 13.41	1.00 25.45	46.3	41
	40x40x28	AS04012HB2856A0(00LAP)	◎	12	0.26	3.12	13000	0.42 14.77	1.16 29.49	48.5	41