



10TB & 8TB | 7200 RPM | SATA 6Gb/s & SAS 12Gb/s

## Highlights

- 10TB capacity<sup>1</sup> in a standard 3.5-inch form factor
- PMR technology works with all capacity enterprise applications & environments
- Reliable, field-proven, 3rd generation design
- Superior power efficiency (Watts/TB)
- Compared to our 8TB air drives
  - 25% more capacity
  - 43% more power efficient (Watts/TB)
  - 25% more reliable (MTBF)
- SATA 6Gb/s and SAS 12Gb/s
  - 12Gb/s SAS compatible with next-gen data centers; backwards compatible with 6Gb/s SAS
- 2.5M hours MTBF<sup>2</sup> rating & 5-year limited warranty
- Instant Secure Erase (ISE) & Self-Encrypting Drive (SED) options

## Applications/Environments

- Enterprise and data center applications where capacity density and power efficiency are paramount
- Cloud & Hyperscale storage
- Massive scale-out high-density data centers (MSO)
- Bulk storage using object storage solutions like Ceph™ and Hadoop® to support Big Data Analytics
- Centralized video surveillance
- Drop-in ready for all mainstream enterprise capacity applications

## Industry's Best Capacity, Power Efficiency and Reliability Delivers Value to the Data Center

Laying the foundation for a worry-free data center, Western Digital delivers an exceptional capacity hard drive for the enterprise – Ultrastar DC HC510, previously known as Ultrastar He10 and part of our HC500 series of helium-filled hard drives. Designed to handle workloads up to 550TB per year, the Ultrastar DC HC510 uses PMR technology and is the industry's first 10TB drive that is drop-in ready for any enterprise-capacity application or environment. Based on field proven, third-generation HelioSeal® technology, it offers one of the lowest power profiles in the industry to help data center architects meet eco-environmental goals and requirements. Targeted at 2.5M hours MTBF, the DC HC510 provides the highest reliability rating available of all HDDs on the market today by building on the successful design of its 8TB and 6TB predecessors. Trust Western Digital and Ultrastar DC HC510 to deliver more capacity, more efficiency, more reliability and more value to your data center.

## HelioSeal® Technology Helps Solve Challenges Facing Next Generation Data Centers

Data centers are facing growing pressures. Data volume is expanding, operating costs are rising, yet budgets remain flat. Lowering the total cost of ownership (TCO) has become the focus of data center architects and the Ultrastar DC HC510 provides the best value proposition and greatest storage efficiency available. Compared to our 8TB air-filled drives, this HelioSeal hard drive provides 25% more capacity, uses 28% less idle power, is 43% more power efficient (Watts/TB), and is 25% more reliable, rated at 2.5M hours MTBF. New features include a second-generation, dual-stage actuator—the Western Digital Micro-Actuator—enhancing head-positioning accuracy to deliver better performance, data integrity and overall drive reliability, especially in multi-drive environments where operational vibration is present. Refer to our technical brief to learn more. A choice of 6Gb/s SATA and 12Gb/s SAS interface enables easy integration into high performance data centers.

## Data Durability and Security with Industry-Leading Quality and Reliability

As drive capacity grows beyond single-digit TBs, object storage systems with erasure coding provide better data durability compared to RAID systems, given its tolerance for simultaneous errors conditions. Ultrastar DC HC510 is a best-fit for object storage implementations given its massive capacity and industry-leading reliability rating. Compliance and privacy requirements drive the need for increased data security. Ultrastar DC HC510 offers security and encryption options to protect data from unauthorized use, including a new option for TCG support on some SATA models.

## Western Digital Quality and Service

Ultrastar DC HC510 extends Western Digital's long-standing tradition of performance and capacity leadership. The proven drive design enables high reliability and availability to customer data. Ultrastar quality, performance and world class technical service and support provides customers with a lower total cost of ownership over previous generations. Ultrastar drives are backed by an array of technical support and services, which may include customer and integration assistance. Dedicated to providing a complete portfolio of devices and systems, Western Digital products help create environments for data to thrive.

**25%**

MORE CAPACITY\*

**43%**

LOWER WATTS/TB\*

**25%**

MORE RELIABLE\*

\*Compared to 8TB air-filled Ultrastar hard drives

## Features & Benefits

Feature / Function	Benefits
<b>Capacity</b>	<ul style="list-style-type: none"> <li>• 10TB and 8TB</li> <li>• 10TB provides 25% more capacity than 8TB drives</li> </ul>
<b>Power Efficiency</b>	<ul style="list-style-type: none"> <li>• Very low Watts per terabyte (W/TB)</li> <li>• 43% lower idle W/TB than our 8TB air drives</li> </ul>
<b>Performance</b>	<ul style="list-style-type: none"> <li>• Dual-Stage Micro Actuator</li> <li>• Rotational Vibration Safeguard (RVS)</li> <li>• NVC Quick Cache (SAS only)</li> <li>• Media cache architecture</li> <li>• Rebuild Assist mode</li> <li>• SATA 6Gb/s &amp; SAS 12Gb/s</li> <li>• 256MB cache buffer</li> <li>• More accurate head positioning, especially in multi-drive environments, for better performance, data integrity and reliability</li> <li>• Maintains drive performance in high rotational vibration environments and multi-drive systems</li> <li>• Better random write performance</li> <li>• Dramatically improves RAID recovery time and maintains system performance during recovery</li> <li>• Provides compatibility with high-performance data centers</li> <li>• Improves response time and data management</li> </ul>
<b>Reliability</b>	<ul style="list-style-type: none"> <li>• Dual safe firmware</li> <li>• 2.5M hours MTBF<sup>2</sup> and 0.35% AFR<sup>2</sup></li> <li>• 5-year limited warranty</li> <li>• Retains previous firmware version for safe firmware updates</li> <li>• Industry's highest reliability rating for Capacity Enterprise HDD for fewer failures/less service needs</li> </ul>
<b>Data Security</b>	<ul style="list-style-type: none"> <li>• Instant Secure Erase</li> <li>• New TCG option for SATA models</li> <li>• Enables swift and efficient drive redeployment and retirement</li> <li>• Hardware-based encryption protects data from unauthorized use</li> </ul>

## Specifications

	SATA Models	SAS Models
<b>Model No.</b>	HUH7210xxALE60y HUH7210xxALN60y	HUH7210xxAL420y HUH7210xxAL520y
<b>Configuration</b>		
<b>Interface</b>	SATA 6Gb/s	SAS 12Gb/s
<b>Capacity<sup>1</sup> (TB)</b>	10TB / 8TB	←
<b>Format: Sector size<sup>3</sup> (bytes)</b>	4Kn: 4096 512e: 512	4Kn: 4096, 4112, 4160, 4224 512e: 512, 520, 528
<b>Max. Areal density (Gbits/sq. in.)</b>	816 (10TB)	←
<b>Performance</b>		
<b>Data buffer<sup>4</sup> (MB)</b>	256	←
<b>Rotational speed (RPM)</b>	7200	←
<b>Latency average (ms)</b>	4.16	←
<b>Interface transfer rate (MB/s, max)</b>	600	1200
<b>Sustained transfer rate<sup>5</sup> (MiB/s, typical)</b>	237 / 215	←
<b>(MB/s, typical)</b>	249 / 225	←
<b>Seek time<sup>6</sup> (read/write, ms, typical)</b>	8.0/8.6	←
<b>Reliability</b>		
<b>Error rate (non-recoverable, bits read)</b>	1 in 10 <sup>15</sup>	←
<b>Load/Unload cycles (at 40°C)</b>	600,000	←
<b>Availability (hrs/day x days/wk)</b>	24x7	←
<b>MTBF<sup>2</sup> (M hours)</b>	2.5	←
<b>Annualized Failure Rate<sup>2</sup> (AFR)</b>	0.35%	←
<b>Warranty (yrs)</b>	5	←

<sup>1</sup> One megabyte (MB) is equal to one million bytes, one gigabyte (GB) is equal to 1,000MB (one billion bytes), and one terabyte (TB) is equal to 1,000GB (one trillion bytes) when referring to storage capacity. Accessible capacity will vary from the stated capacity due to formatting, system software, and other factors.

<sup>2</sup> MTBF and AFR specifications are based on a sample population and are estimated by statistical measurements and acceleration algorithms under typical operating conditions for this drive model.

MTBF and AFR ratings do not predict an individual drive's reliability and do not constitute a warranty.

<sup>3</sup> Advanced Format drive: 4K (4096-byte) physical sectors

<sup>4</sup> Portion of buffer capacity used for drive firmware

<sup>5</sup> MiB/s is 2<sup>20</sup> bytes, MB/s is 10<sup>6</sup> bytes

<sup>6</sup> Excludes command overhead

<sup>7</sup> SATA models: 8K Queue Depth = 1 @ 40 IOPS, SAS models: 4K Queue Depth = 4 @ Max IOPS

<sup>8</sup> Idle specification is based on use of Idle\_A

	SATA Models	SAS Models
<b>Acoustics</b>		
<b>Idle (Bels, typical)</b>	2.0/3.6	←
<b>Power</b>		
<b>Requirement</b>	+5 VDC, +12VDC	←
<b>Operating<sup>7</sup></b>	6.8	9.5
<b>Idle<sup>8</sup> (W)</b>	5.0	5.8
<b>Power consumption efficiency at Idle (W/TB) (Watts/TB)</b>	0.50	0.58
<b>(Watts/GB)</b>	0.00050	0.00058
<b>Physical Size</b>		
<b>z-height (mm)</b>	26.1	←
<b>Dimensions (width x depth, mm)</b>	101.6 (+/-0.25) x 147	←
<b>Weight (g, max)</b>	660	←
<b>Environmental (Operating)</b>		
<b>Ambient temperature</b>	5° to 60° C	←
<b>Shock (half-sine wave 2 ms, G)</b>	70	←
<b>Vibration (G RMS 5 to 500 Hz)</b>	0.67 (XYZ)	←
<b>Environmental (Non-Operating)</b>		
<b>Ambient temperature</b>	-40° to 70° C	←
<b>Shock (half-sine wave, G)</b>	300 (2ms) / 150 (11ms)	←
<b>Random vibration (G RMS 2 to 200 Hz)</b>	1.04 (XYZ)	←

NOTE: See "How to read the Ultrastar model number" below for possible values for xx and y.

### How to Read the Ultrastar Model Number

Example: HUH7210xxAL420y = 7200 RPM, xxTB, 4Kn SAS 12Gb/s

H = Western Digital	42 = Interface, 4Kn SAS 12Gb/s
U = Ultrastar	(52 = 512e SAS 12Gb/s, E6 = 512e SATA 6Gb/s, N6 = 4Kn SATA 6Gb/s)
H = Helium (vs. S for Standard)	0 = Reserved
72 = 7200 RPM	y = Data Security Mode
10 = Full capacity—10TB (10,000GB)	0 = Instant Secure Erase
xx = Capacity this model (10 = 10TB, 08 = 8TB)	1 = Self-encrypting Drive (SED)**
A = Generation code	4 = Secure Erase (overwrite only)
L = 26.1mm z-height	5 = TCG encryption with FIPS (SAS)

\*\* Bulk Data Encryption+TCG (SATA), TCG (SAS)

## Western Digital.

5601 Great Oaks Parkway  
San Jose, CA 95119, USA  
**US (Toll-Free):** 800.801.4618  
**International:** 408.717.6000

www.wdc.com/dc-hc510  
www.wdc.com/dc-support

© 2015-18 Western Digital Corporation or its affiliates. All rights reserved. Published 12/15, Rev 7/18. Western Digital, the Western Digital logo, HelioSeal and Ultrastar are registered trademarks or trademarks of Western Digital Corporation or its affiliates in the U.S. and/or other countries. Other marks are property of their respective owners. References in this publication to Western Digital products, programs, or services do not imply that they will be made available in all countries. Product specifications provided are sample specifications that are subject to change and do not constitute a warranty. Please visit the Support section of our website, www.wdc.com/dc-support, for additional information on product specifications. Pictures shown may vary from actual products.