



## 8-Port Gigabit Desktop/Rackmount Switch with 8-Port PoE

TL-SG1008PE

### ■ Overview

The TL-SG1008PE is an 8-Port Gigabit Desktop/Rackmount Switch with all 8 ports PoE+ supported, it provides a simple means of expanding a wired network through transferring power and data over a single Ethernet Cable. With total power budget of 124W, up to 30W per port, TL-SG1008PE can power up more high power PDs such as wireless Access Points (APs), IP Cameras or IP Phones. Moreover, with the innovative energy-efficient technology, the TL-SG1008PE can save up to 75% of the power consumption, making it an eco-friendly solution for your business network.

**Power Over Ethernet**

- IEEE802.3af standard
- IEEE802.3at standard
- Supports PoE+ power up to 30W for each PoE+ port
- Supports PoE+ power up to 124W for all PoE+ ports
- Supports Priority function to protect the system when the system power is overloaded

**High Performance**

- Auto-MDI/MDIX
- Auto-negotiation
- Store and forward
- IEEE 802.3x flow control for Full-duplex Mode
- Backpressure for Half-duplex Mode
- 8k MAC address auto-learning and auto-aging

**Easy to use**

- Plug and Play design



- Details:<http://www.tp-link.com/support/Localesupport.asp>
- German/Austrian/Swiss users are not included



## 8-Port Gigabit Desktop/Rackmount Switch with 8-Port PoE

### TL-SG1008PE

**Power Over Ethernet**

All 8 Auto-Negotiation RJ45 ports of the switch support Power over Ethernet Plus(PoE+) function. These PoE+ ports can automatically detect and supply power with those IEEE 802.3af/at compliant Powered Devices (PDs).

**- Overload Arrangement**

TL-SG1008PE has the priority function which will help protect the system when the system power is overloaded. If all PoE PDs power consumption is  $\geq 124W$ , a priority will be arranged among the PoE+ ports, then the system will cut off the power of the lowest-priority port.


**- Port Priority Function**

Priority (port 1>port 2>port 3>port 4>port 5>port 6>port 7>port 8): This function will help protect the system if the system power becomes overloaded. For example, Port 1, 2, 4 and 7 are using 30w (maximum power per port is 30W), the system power is 120w in total (PoE+ max LED is red ). If there is an additional PD inserted to Port 3 with 25w then the system will cut off Port 7 to protect the system, this means Port 1, 2 and 4 will use 30w, and Port3 will use 25w, and no power will be supplied to Port 7.

**Easy To Use**

TL-SG1008PE is easy to install and use. It requires no configuration and installation. With desktop/Rackmount design, outstanding performance and quality, the TP-LINK TL-SG1008PE 8-Port Gigabit Desktop/Rackmount Switch with 8-Port PoE is a great selection for expanding your home or office network.

## Specifications

Hardware Features & Performance	
<b>Product Picture</b>	
<b>Model</b>	TL-SG1008PE
<b>Standards</b>	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x, IEEE 802.3af, IEEE 802.3at
<b>Network Ports</b>	8*10/100/1000Mbps RJ45 ports with 8 PoE ports
<b>Network Media(Cable)</b>	10Base-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 100Base-TX: UTP category 5, 5e or above cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 1000Base-T: UTP category 5, 5e cable or above cable(maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
<b>Auto Negotiation</b>	YES
<b>Auto MDI/MDIX</b>	YES
<b>PoE Power on RJ45</b>	Power+: pin 3 & pin 6 Power -: pin 1 & pin 2
<b>Power Consumption</b>	9.5 watts (max. no PD connected) 140.1 watts (max. with 124w PD connected)
<b>Forwarding Mode</b>	Store and Forward
<b>Switch Capacity</b>	16Gbps
<b>MAC Address Table</b>	8k, Auto-learning, Auto-aging
<b>Flow Control</b>	YES
<b>Backpressure</b>	YES
<b>Fan Quantity</b>	1
<b>LED</b>	Power, 1000Mbps, Link/Act, PoE Status, PoE MAX
<b>Dimensions</b>	11.6*7.1*1.7 in. (294*180*44 mm)
<b>Certification</b>	CE,FCC
<b>Systems</b>	Windows 2000/XP/Vista/7/8 Linux/MAC OS
<b>Operating Temperature</b>	0°C ~40 °C (32 °F ~104°F )
<b>Storage Temperature</b>	-40 °C ~70 °C (-40 °F ~158°F )
<b>Operating Humidity</b>	10%~90% non-condensing
<b>Storage Humidity</b>	5%~90% non-condensing

## Ordering Information

Host Switches	
<b>Product Model</b>	Description
TL-SG1008PE	8-Port Gigabit Desktop/Rackmount Switch with 8-Port PoE
TL-SG1008P	8-Port Gigabit Desktop Switch with 4-Port PoE
PoE Adapter	
<b>Product Model</b>	Description
TL-POE10R	PoE Splitter
Router	
<b>Product Model</b>	Description
TL-ER604W	SafeStream Wireless N Gigabit Broadband VPN Router
TL-ER608W	SafeStream Wireless N Gigabit Broadband VPN Router