



8/16/24/48-Port 10/100Mbps + 2/1/2/3-Port Gigabit Switch

TL-SL1210 / TL-SL1117 / TL-SL1226 / TL-SL1351

Overview

The TL-SL1210/TL-SL1117/TL-SL1226/TL-SL1351 with TP-LINK Green Technology is an environmental-friendly and competitive choice for small business. It provides 8/16/24/48 10/100Mbps RJ45 ports and 2/1/2/3 gigabit uplink ports, and all RJ45 ports support Auto-MDI/MDIX. TL-SL1210/TL-SL1117/TL-SL1226/TL-SL1351 provides a cost-effective, high performance, non-disruptive, smooth evolution into Gigabit solutions. Moreover, with the innovative energy-efficient technology, the TL-SL1210/TL-SL1117/TL-SL1226 can save up to 75%/70%/60%* of the power consumption and 80% of the packaging material can be recycled, making it an eco-friendly solution for your business network.

Green Technology

- Saving power 75%/70%/60%
- Recyclable packaging material

High Performance

- IEEE 802.3x flow control
- Non-blocking switching architecture
- 5.6/5.2/8.8/15.6 Gbps Switching Capacity
- Store and forward
- Auto-MDI/MDIX
- Auto-negotiation
- MAC address auto-learning and auto-aging

Easy to use

- Plug and Play design
- Quiet/Fanless design



8/16/24/48-Port 10/100Mbps + 2/1/2/3-Port Gigabit Switch

TL-SL1210 / TL-SL1117 / TL-SL1226 / TL-SL1351

TP-LINK Green Technology

This new generation TL-SL1210/TL-SL1117/TL-SL1226 features the latest innovative energy-efficient technologies that can greatly expand your network capacity with much less power. It automatically adjusts power consumption according to the link status and cable length to limit the carbon footprint of your network. It also complies with the EU'S RoHS, prohibiting the use of certain hazardous materials. Besides, 80% of the packaging material can be recycled.

High Performance

The TL-SL1210/TL-SL1117/TL-SL1226/TL-SL1351 has 8/16/24/48 fast Ethernet ports and 2/1/2/3 gigabit uplink ports. The gigabit uplink port provides bandwidth up to 1000Mbps which can provide large file transferring and also be compatible with 10Mbps and 100Mbps Ethernet devices. Featuring non-blocking switching architecture, TL-SL1210/TL-SL1117/TL-SL1226/TL-SL1351 forwards and filters packets at full wire-speed for maximum throughput. And IEEE 802.3x flow control for Full Duplex mode and backpressure for Half Duplex mode alleviate the traffic congestion and make TL-SL1210/TL-SL1117/TL-SL1226/TL-SL1351 work reliably. It's a perfect choice to update your network to Gigabit while protecting your previous investment properly.





Easy to Use

The auto features of this switch make installation plug and play and hassle-free. No configuring is required. Auto MDI/MDIX eliminates the need for crossover cables. Auto-negotiation on each port senses the link speed of a network device (10, 100, or 1000 Mbps) and intelligently adjusts for compatibility and optimal performance.



- Details:<http://www.tp-link.com/support/Localesupport.asp>
- German/Austrian/Swiss users are not included

Specifications:

Product Picture				
Model	TL-SL1210	TL-SL1117	TL-SL1226	TL-SL1351
Standards	IEEE 802.3 IEEE 802.3u IEEE 802.3ab IEEE 802.3x	IEEE 802.3 IEEE 802.3u IEEE 802.3ab IEEE 802.3x	IEEE 802.3 IEEE 802.3u IEEE 802.3ab IEEE 802.3x	IEEE 802.3 IEEE 802.3u IEEE 802.3ab IEEE 802.3x IEEE 802.3z
Network Ports	8*10/100Mbps RJ45 ports+ 2*10/100/1000Mbps RJ45 ports	16*10/100Mbps RJ45 ports+ 1*10/100/1000Mbps RJ45 port	24*10/100Mbps RJ45 ports+ 2*10/100/1000Mbps RJ45 ports	48*10/100Mbps RJ45 ports+ 3*10/100/1000Mbps RJ45 ports
Auto Negotiation	YES	YES	YES	YES
Auto MDI/MDIX	YES	YES	YES	YES
Systems	Windows 2000/XP/Vista/7 Linux/MAC OS	Windows 2000/XP/Vista/7 Linux/MAC OS	Windows 2000/XP/Vista/7 Linux/MAC OS	Windows 2000/XP/Vista/7 Linux/MAC OS
Forwarding Mode	Store and Forward	Store and Forward	Store and Forward	Store and Forward
Switch Capacity	5.6 Gbps	5.2 Gbps	8.8 Gbps	15.6 Gbps
MAC Address Table	8 K	8 K	8 K	8 K
Flow Control	YES	YES	YES	YES
Fanless	YES	YES	YES	YES
Power Saving	Up to 75%	Up to 70%	Up to 60%	No
LED	Power、 1000Mbps、 Link/Act	Power、 1000Mbps、 Link/Act	Power、 1000Mbps、 Link/Act	Power、 Link/Act
Dimensions	294*180*44 mm	440*180*44mm	440*180*44mm	440*180*44mm
Operating Temperature	0°C~40°C (32°F~104°F)	0°C~40°C (32°F~104°F)	0°C~40°C (32°F~104°F)	0°C~40°C (32°F~104°F)
Storage Temperature	-40°C~70°C (-40°F~158°F)	-40°C~70°C (-40°F~158°F)	-40°C~70°C (-40°F~158°F)	-40°C~70°C (-40°F~158°F)
Operating Humidity	10%~90% non-condensing	10%~90% non-condensing	10%~90% non-condensing	10%~90% non-condensing
Storage Humidity	5%~90% non-condensing	5%~90% non-condensing	5%~90% non-condensing	5%~90% non-condensing
Ordering Information	8-Port 10/100Mbps + 2-Port Gigabit Switch	16-Port 10/100Mbps + 1-Port Gigabit Switch	24-Port 10/100Mbps + 2-Port Gigabit Switch	48-Port 10/100Mbps + 3-Port Gigabit Switch

* Maximum power savings when compared to a TP-LINK conventional switch, the real saving rate may vary based on the usage condition.