

# QNAP TS-1253U 12-BAY

<b>Processor</b>	Quad-core Intel® Celeron® 2.0GHz (up to 2.42GHz) Installed: 4GB DDR3L SDRAM (1 x 4GB) Slots: 2 SODIMM (Max: 8GB)
<b>Memory</b>	NOTE: 1. When installing two memory modules, please ensure that they are the same size and ideally use the same type of RAM for both memory slots. 2. For the information of RAM module installation and compatible NAS models, please refer to the <a href="#">QNAP RAM Module Installation Guide</a>
<b>Flash memory</b>	512MB 12 x 3.5" or 2.5" SATA 6Gb/s, SATA 3Gb/s hard drive or SSD
<b>Internal drive</b>	NOTE: 1. The system is shipped without HDD. 2. <a href="#">HDD compatibility list</a>
<b>Drive tray</b>	12 Hot-swappable and lockable trays
<b>Network interface</b>	4 RJ45 Gigabit Ethernet ports
<b>Ports</b>	4 USB 3.0 1 HDMI 1 console (system maintenance)
<b>LED indicators</b>	Status, LAN, USB, HDD 1-12
<b>Buttons</b>	Power, reset
<b>Alarm buzzer</b>	System warning
<b>Form factor</b>	2U, rack mountable
<b>Dimensions</b>	89 (H) x 482 (W) x 534 (D) mm 3.5 (H) x 18.98 (W) x 21.02 (D) inch
<b>Weight</b>	Net weight: 16.14 kg (35.58 lbs.) Gross weight: 18.98 kg (41.84 lbs.)
<b>Power consumption (W)</b>	HDD standby: 35.14W In operation: 83.52W (with 12 x 2TB HDD installed)
<b>Sound Level*</b>	Sound pressure (LpAm) :35.2 dB(A)
<b>Temperature</b>	0-40°C
<b>Humidity</b>	0~95% R.H.
<b>Power supply</b>	Input: 100-240V AC, 50/60Hz; Output: 250W
<b>Fan</b>	2 x 70mm, 12V DC