


## Application

- For **outdoor and indoor** use in structured (data) wiring systems such as **campus backbone, building backbone (riser)** and/or horizontal cabling.
- For **outdoor and indoor** use in networks for telecom, cable TV and/or broadcast.
- **Easy to install** in ducts, tunnels, trenches and/or tubes (by means of compressed air or pulling wire). Suitable for **direct burial** (crush  $\leq 150$  N/cm).

## Key features

- A simple **all dielectric** cable construction (and consequently **more cost-effective up to 24 fibres** than multi-tube cables) with **improved rodent protection**.
- These cables are **halogen-free** (= FRNC and LSNH) and therefore suitable for both outdoor and indoor use. Consequently **splicing can be avoided** and the installation gets **more cost-effective**.
- **Predicted life time > 30 years**.

## Construction & dimensions



**Cable specifications** (construction in accordance with IEC 60794)

1. Primary coated optical fibres:  $\text{Ø } 250 \pm 15 \mu\text{m}$ .
2. Central tube, jelly filled (**non dripping and silicon-free**) with **up to 24 fibres**.  
 Individually colour coded optical fibres:  
 1 – 12: red - natural - yellow - blue - green - violet - brown - black - orange - turquoise - pink and white  
 13 – 24: red - natural - yellow - blue - green - violet - brown - grey - orange - turquoise - pink and white **with black rings**.
3. Swellable yarns as strength members and for the **longitudinal watertightness** and **improved rodent protection**.
4. **Orange** halogen-free (FRNC/LSNH) outer jacket.  
 Identification: BELDEN OFC – "cable type" – "number x type of fibre" + date-, meter- and P/N-marking.

### Mechanical data

	<b>improved rodent protection</b>
<b>No. of fibres</b>	<b>4 - 8 - 12 - 24</b>
Ø Central tube (mm)	4.2
Ø nom./max. (mm)	10.2 / 10.5
Weight (kg/km)	104
Energy of flame (kJ/m)	1680

## Ordering information

### Belden Europe code

Fibre-type/-count	<b>4</b>	<b>6</b>	<b>8</b>	<b>12</b>	<b>24</b>
9/125			43860	43863	43868
50/125	43856	43858	43861	43864	43869
62.5/125	43857	43859	43862	43865	43870
Colour code (orange)	3040	3040	3040	3040	3040
Reel code	042	042	042	042	042
Std. delivery length	2100 $\pm$ 100 m				



## Optical characteristics

### Characteristics (cabled) Multi-Mode -) Graded-Index optical fibres according to IEC 60793

Fibre-type	Size ( $\mu\text{m}$ )	Wavelength (nm)	Attenuation average/max. (dB/km)	Bandwidth (MHz•km)	Gigabit Ethernet Performance (m)	Refractive Index
50/125	50 $\pm$ 2.5	850	2.5 / 2.7	$\geq$ 600	550	1.481
	125 $\pm$ 2	1300	0.5 / 0.8	$\geq$ 1200	550	1.476
62.5/125	62.5 $\pm$ 2.5	850	3.0 / 3.2	$\geq$ 200	220	1.495
	125 $\pm$ 2	1300	0.6 / 0.9	$\geq$ 600	550	1.490

Fibres with improved Gigabit Ethernet performance on request available.

### Characteristics (cabled) Single-Mode ( Matched-Cladded optical fibres according to ITU-G.652

Fibre-type	Size ( $\mu\text{m}$ )	Wavelength (nm)	Attenuation average/max. (dB/km)	Dispersion (ps/(nm•km))	PMD (ps/ $\sqrt{\text{km}}$ )	Refractive Index
9/125	9.3 $\pm$ 0.5	1310	0.33 / 0.38	$\leq$ 3.5		1.467
	125 $\pm$ 1	1550	0.20 / 0.25	$\leq$ 18	$\leq$ 0.5	1.467

A test report (attenuation) is supplied with each delivery.

## Mechanical, physical and/or environmental

### Temperature range according to IEC 60794-1-2-F1

Transport/storage	- 30 to + 70 °C
Installation	- 5 to + 50 °C
Operation	- 30 to + 70 °C

### Watertightness according to IEC 60794-1-2-F5

### Pulling tension according to IEC 60794-1-2-E1

Cable with improved RP	$\leq$ 4000 N
------------------------	---------------

### Crush resistance according to IEC 60794-1-2-E3

Cable	$\leq$ 15000 N/m
-------	------------------

### Bending radii for fibres and tubes

Installation/operation	$>$ 25 mm
------------------------	-----------

### Bending radii cable

Static according to IEC 60794-1-2-E11	– 10 x $\varnothing$
Dynamic according to IEC 60794-1-2-E6	– 15 x $\varnothing$

### Halogen-free according to HD 602 (IEC 60754-2)

Corrosivity	pH $\geq$ 3.5 - $\mu\text{S/cm} \leq$ 100
-------------	---

### Flame retardancy according to IEC 60332-3C

## Guide to installation and handling

- When laying and installing optical fibre cables **it is vitally important not to exceed the specified values** set for pulling tension, bending radii and temperature.  
The installation methods have to be in accordance with the common standards.
- To ease insertion into tubes by means of compressed air or pulling wire, certified lubricants (e.g. paraffin) may be used. The use of soap or similar substances as lubricants is strictly prohibited.
- If a cable needs to be fastened, constrictions  $\geq$  0.3 mm must be prevented.
- The jelly filling inside the tubes can be removed using a tissue soaked in turpentine.
- It is advisable to cap the cable-ends during storage.

## Options

- Cables from **1 to 24 fibres**.
- Cables with a PE jacket for outdoor use.
- **Non-standard cable constructions**, colours, details and/or additional information regarding specifications are available on request.