



LAMP PART NO.	COLOR WHITE 6900°KELVIN	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS) (AVG.)
BF20125-28B	x = .325 y = .295	700 @ 0°C	280	5	38,000 TYP.	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC THIRD ANGLE PROJECTION	DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		COMPONENTS CORPORATION						
				TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP								
			DRAWN BY L. WENGSTROM	APPV'D BY J.K.	DATE 4/22/04	SIZE A	FSCM NO. 55335	DRAWING NO. BF20125-28B				
RELEASE & CANCEL P-0404-14			4/22/04									
REV. NO.	DESCRIPTION/ECO NUMBER		APPV'D DATE			- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE	RELEASED DATE 4/22/04	REVISION DATE	REV. NO.	SHEET 1 OF 1