


LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m <sup>2</sup> )	*RATED LIFE (HRS)
BF20218-24B	LCD HIGH OUTPUT WHITE 8400°k RGB	1700 @ 0°C	740	5	38,000 ± 10%	20,000

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			<b>METRIC</b>  THIRD ANGLE PROJECTION	DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		<b>COMPONENTS CORPORATION</b>						
				TITLE <b>MINIATURE COLD CATHODE FLUORESCENT LAMP</b>								
A CHANGE MECH. ART			DRAWN BY L. WENGSTROM	APPV'D BY L.W.	DATE 1/21/03	SIZE A	FSCM NO. 55335	DRAWING NO. BF20218-24B				
RELEASED			11/4/02			SCALE NONE			RELEASED DATE 11/4/02	REVISION DATE 1/21/03	REV. NO. A	SHEET 1 OF 1
REV. NO.	DESCRIPTION/ECO NUMBER		APPV'D DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED								