


LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF20226-24B	LCD HIGH OUTPUT WHITE 8400°k RGB	1730 @ 0°C	745	5	38,000 ± 10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC  THIRD ANGLE PROJECTION	DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		COMPONENTS CORPORATION						
				TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP								
			DRAWN BY L. WENGSTROM	APPV'D BY F.D.	DATE 1/16/03	SIZE A	FSCM NO. 55335	DRAWING NO. BF20226-24B				
RELEASED			1/16/03			SCALE NONE			RELEASED DATE 1/16/03	REVISION DATE	REV. NO.	SHEET 1 OF 1
REV. NO.	DESCRIPTION/ECO NUMBER		APPV'D DATE		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED							