


PART NUMBER	-A- LENGTH	LCD HIGH OUTPUT WHITE RGB COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF26188-20B	188±3.0	5,400°k x = .336 y = .353	1115 @ 0°C	405	5 ± 1	30,000 TYP.	35,000 AVG.
BF26214-20B	214±2.0		1150 @ 0°C	460			
BF26285-20B	285±2.0		1525 @ 0°C	610			
BF26318-20B	318±1.5		1710 @ 0°C	685			
BF26360-20B	360±1.5		1940 @ 0°C	775			

NOTES:

* RATED LIFE IS DEFINED AS THE POINT WHICH INTENSITY BECOMES 50% OF THE INITIAL RATING.

RATING AT 25°C UNLESS OTHERWISE SPECIFIED.

METRIC



THIRD ANGLE PROJECTION

DIMENSIONS ARE IN MILLIMETERS

TOLERANCE UNLESS OTHERWISE SPECIFIED

1 PL +/- REF.
2 PL +/- REF.
ANGLE +/- REF.

DRAWN BY
L. WENGSTROM

APP'VD BY DATE
J.K. 10/20/04

SIZE
A

FSCM NO.
55335

DRAWING NO.

BF 26-20B

- CAD DRAWING -

MANUAL REVISIONS NOT PERMITTED

SCALE

NONE

RELEASED DATE

8/14/03

REVISION DATE

10/20/04

REV. NO.

A

SHEET
1 OF 1

COMPONENTS CORPORATION

TITLE

**MINIATURE COLD CATHODE
FLUORESCENT LAMP**

A

ELECTRICAL CHNG. & ADD BF26318 & BF26360

10/20/04

REV. NO.

RELEASED TO CAD MULTI LIST

8/14/03

DESCRIPTION/ECO
NUMBER

APP'VD
DATE