



PART NUMBER	-A- LENGTH	LCD HIGH OUTPUT WHITE RGB COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF26180-24B	180±3.0	11000°k	1000 @ 0°C	400	5 ± 1	38,000±10%	20,000
BF26188-24B	188±3.0	11000°k	1000 @ 0°C	420	5 ± 1	30,000±10%	20,000
BF26214-24B	214±2.0	9200°k	1450 @ 0°C	620	5 ± 1	30,000±10%	20,000
BF26230-24B	230±3.0	11000°k	1175 @ 0°C	495	5 ± 1	30,000±10%	20,000
BF26240-24B	240±3.0	11000°k	1250 @ 0°C	505	5 ± 1	30,000±10%	20,000
BF26250-24B	250±5.0	11000°k	1300 @ 0°C	525	5 ± 1	30,000±10%	20,000

METRIC THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0		COMPONENTS CORPORATION TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP						
		DRAWN BY L. WENGSTROM						APPV'D BY DATE L.W. 8/14/03		SIZE A
RELEASED TO CAD MULTI LIST 8/14/03		APPV'D DATE		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE	RELEASED DATE 8/14/03	REVISION DATE	REV. NO.	SHEET 1 OF 1