

LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)	
BF26180-24B	LCD HIGH OUTPUT WHITE 11000°k RGB	1000 @ 0°C	400	5	38,000 ± 10%	20,000	

<sup>\*</sup> RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

		METRIC	DIMENSIONS ARE							
			( <del>-</del>	TOLERANCE UNLESS		COMPONENTS CORPORATION				
	1	ĺ		OTHERWISE SPECIFIED 1 PL +/- 0	TITLE	MIN	IATURE COLI	D CATHODE		
			THIRD ANGLE PROJECTION	2 PL +/- 0 ANGLE +/- 0		FLUORESCENT LAMP				
			DRAWN BY	APPV'D BY DATE	SIZE	1	DRAWING NO.	06400 04D		
A	DIM LINE CORRECT. AND 180+/-5.0 TO 180+/-3.0 RELEASED	10/17/00 5/23/00			Α	55335		26180-24B		
REV NO.	DESCRIPTION/ECO	APPV'D DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE		DATE 5/23/00	REVISION DATE 10/17/00	NO. A	1 OF 1