


LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF26285-20B	LCD HIGH OUTPUT WHITE 5600°k RGB	1700 @ 0°C	725	5	30,000 ± 10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			<div>METRIC</div> <div></div> <div>THIRD ANGLE PROJECTION</div>		<div>DIMENSIONS ARE IN MILLIMETERS</div> <div>TOLERANCE UNLESS OTHERWISE SPECIFIED</div> <div>1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0</div>		COMPONENTS CORPORATION						
							TITLE						
							MINIATURE COLD CATHODE FLUORESCENT LAMP						
A	CIRCUIT VOLTS & BRIGHTNESS CHNG-CONVERT TO CAD DRAWING		5/18/01	DRAWN BY L. WENGSTROM	APPVD BY DATE FD 5/18/01	SIZE A	FSCM NO. 55335	DRAWING NO. BF26285-20B					
	RELEASED		4/13/99	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE	RELEASED DATE 4/13/99		REVISION DATE 5/18/01		REV. NO. A	SHEET 1 OF 1	
REV. NO.	DESCRIPTION/ECO NUMBER		APPVD DATE										