

LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF26318-20B	LCD HIGH OUTPUT WHITE 5300°k RGB	1636 @ 0°C	676	5	34,000 ± 10%	20,000

^{*} RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

	THII		METRIC	DIMENSION IN MILLIN				G015701			
				TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0		COMPONENTS CORPORATION					ION
						TITLE	MINIATURE COLD CATHODE				
			THIRD ANGLE PROJECTION		2 PL +/- 0 ANGLE +/- 0 FLUORESCENT LAMP						
				APPV'D BY	DATE	SIZE	FSCM NO.				
			L. WENGSTROM	F.D.	2/28/02	Α	55335	NO. BF	26318-20B		
REV.	RELEASED DESCRIPTION/ECO	2/28/02 APPV'D	- CAD DRAWING -		-	SCALE		RELEASED	REVISION	REV.	SHEET
NO.	NUMBER	DATE	MANUAL REVISIONS NOT PERMITTED				NONE	DATE 2/28/02	DATE	NO.	1 _{OF} 1