



PART NUMBER	LENGTH A +/- 2mm	COLOR (REF.)	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF5118-20B	118mm	RGB HIGH OUTPUT WHITE 5400° KELVIN	600	305	5 ± 1	7000 ± 700	20,000
BF5165-20B	165mm		800	400	5 ± 1	7000 ± 700	20,000
BF5200-20B	200mm		850	445	5 ± 1	7000 ± 700	20,000
BF5300-20B	300mm		1000	600	5 ± 1	7000 ± 700	20,000

*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		COMPONENTS CORPORATION			
			DRAWN BY L. WENGSTROM		APPV'D BY JK		DATE 02/29/00		TITLE SINGLE LEAD TIPLESS MINIATURE FLUORESCENT LAMP	
A			6.3 TO 6.2 MAX., ADD 5.0 DIM.		2/29/00		SIZE A		FSCM NO. 55335	
RELEASED - CANCEL BF-5mm DIA DRAWING			2/25/00		2/25/00		DRAWING NO. BF 5-20B			
REV. NO.			DESCRIPTION/ECO NUMBER		APPV'D DATE		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE	
							RELEASED DATE 2/25/00		REVISION DATE 2/29/00	
							REV. NO. A		SHEET 1 OF 1	