


BUSHING MOUNT/SLEEVE BEARING
MODEL 2802

HYBRID SINGLE-TURN PRECISION POTENTIOMETERS

BUSHING MODEL	2802
ELECTRICAL	
Theoretical Electrical Travel	358°
Normal Resistance Range	1.5K to 40K
Extended Resistance Range ⁽¹⁾	750Ω to 50K
Resistance Tolerance: Standard %	± 5
Best Practical %	± 3
Power Rating At 70°C, Derating To 0 At 125°C (Watts)	7.0
Linearity, Independent, Tolerance, Standard %	± 0.15
Best Practical %	± 0.07
Output Smoothness Max. (% Of Total Applied Voltage)	0.15
End Voltage Max. (% Of Total Applied Voltage)	0.25
Insulation Resistance At 500 VDC, Min. (Megohms)	1000
Dielectric Withstanding Voltage (Volts RMS)	1000
Max. Applied Voltage (Volts DC) ⁽²⁾	400
Temperature Coefficient Of Potentiometer, Max. %/°C	± .007
MECHANICAL	
Total Mechanical Travel	360° Continuous
Mechanical Life, Shaft Revolutions	2 million
Ganged Cups, Max. (Number)	8
Taps, Max., Excluding End Terminations	41
Moment Of Inertia, Per Cup (gm-cm ²)	8.5
Weight: Single Cup (oz.)	6.5
Each Additional Cup (oz.)	1.4
Torque, Max. Per Cup (oz.-in)	1.7
Pilot Diameter Runout, Max.	.0015
Lateral Runout, Max.	.005
Shaft Runout, Max.	.001
Shaft Radial Play, Max.	.003
Shaft End Play, Max.	.005
Dimension For Each Additional Cup	.562 ± .002
ENVIRONMENTAL	
Temperature Range (°C) Standard	-55 to +125

(1) All specifications listed apply to units with a total resistance within the normal resistance range. Higher or lower resistances may require some degradation of listed specifications because of resistance material composition.

(2) Not to exceed specified power rating.



ALL MODELS are manufactured to meet or exceed applicable characteristics of MIL-R-39023. For MILITARY-APPROVED (QPL) Listings, see page 52.

TOLERANCES UNLESS OTHERWISE SPECIFIED:

FRACTIONAL: ± 1/64" DECIMAL: ± .005" ANGULAR: ± 1°

2802

