



3079A Paired - DataBus® ISA/SP-50 PROFIBUS Cable

		<p style="text-align: center;">For more information please call</p> <p style="text-align: center;">1-800-Belden1</p> <p style="text-align: center;"><u>See Put-ups and Colors</u></p>
---	--	---

Description:

22 AWG solid bare copper conductors, FHDPE insulation, Beldfoil® (100% coverage) plus a tinned copper braid shield (65% coverage), PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	1
Total Number of Conductors	2
AWG	22
Stranding	Solid
Conductor Diameter	.026 in.
Conductor Material	BC - Bare Copper

INSULATION:

Insulation Material	FRFPE - Flame Retardant Foam Polyethylene
Lay Length	2.75 in.
Pair Diameter	.198 in.

Pair Color Code Chart :

Number	Color
1	Red & Green

OUTER SHIELD:

Outer Shield Material Trade Name	Beldfoil®
Outer Shield Type	Tape/Braid

Outer Shield Material :

Layer Number	Material Trade Name	Type	Material	% Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100
2		Braid	TC - Tinned Copper	65

Outer Shield %Coverage	100 %
------------------------	-------

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

OVERALL NOMINAL DIAMETER:



3079A Paired - DataBus® ISA/SP-50 PROFIBUS Cable

Overall Nominal Diameter	.315 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-30°C To +75°C
UL Temperature Rating	75°C
Bulk Cable Weight	45 lbs/1000 ft.
Max. Recommended Pulling Tension	50 lbs.
Min. Bend Radius (Install)	3.5 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	PLTC, CMG
CEC/C(UL) Specification	CMG
AWM Specification	UL Style 20201 (600 V 75°C)
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004

FLAME TEST:

UL Flame Test	UL1685 FT4 Loading
CSA Flame Test	FT4

ELECTRICAL CHARACTERISTICS:

Fitted Impedance :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Fitted Impedance (Ohms)
		3	20	150

Nom. Mutual Capacitance @ 1 KHz	8.5 pF/ft
Nominal Velocity of Propagation	78 %
Nom. Conductor DC Resistance @ 20 Deg. C	16.0 Ohms/1000 ft
Ind. Pair Nominal Shield DC Resistance @ 20 Deg. C	3.9 Ohms/1000 ft

Nom. Attenuation (dB/100 ft) :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	.2			.27
	4.0			.67
	16.0			1.37

Max. Attenuation (dB/100 m) :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Max. Attenuation (dB/100 m)
	.20			.9
	4.0			2.2
	16.0			4.5



3079A Paired - DataBus® ISA/SP-50 PROFIBUS Cable

Max. Operating Voltage - UL :

UL Voltage	UL
300V	CMG
600V	AWM

Max. Recommended Current :

Description	Max. Recommended Current
Per Conductor	2.3 Amps

Other Electrical Characteristic 1

Capacitance Unbalance @ 1 kHz: Less than 1000 pF/km

NOTES:

Notes

Siemens Sinec L2 Cable. For CPE jacketed version order Part No. YR45047. For LS0H (FRNC) jacketed version, order Part No. YR44731.

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
3079A 0071000	1 PR #22 FRFPE FRPE SH PVC	1000	56	VIOLET	C
3079A 0072000	1 PR #22 FRFPE FRPE SH PVC	2000	112	VIOLET	C
3079A 0073600	1 PR #22 FRFPE FRPE SH PVC	3600	201.6	VIOLET	C
3079A 0601000	1 PR#22FRFPEFRPES HPVC	1000	56	CHROME	C
3079A 0602000	1 PR#22FRFPEFRPES HPVC	2000	112	CHROME	C
3079A 0603600	1 PR#22FRFPEFRPES HPVC	3600	201.6	CHROME	C

C = CRATE REEL PUT-UP.

Revision Number: 1

Revision Date: 10-05-2005



3079A Paired - DataBus® ISA/SP-50 PROFIBUS Cable

© 2005 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden CDT Electronics Division believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden CDT Electronics Division declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.