



**7929A Paired - Category 5e DataTuff® Twisted Pair Cable**

|  |   |
|--|---|
|   | <p>For more information please call<br/><b>1-800-Belden1</b></p> <p><u>See Put-ups and Colors</u></p> <p><b>Color Code Chart : No. 8 for DataTwist Cables (Modified Western Electric).pdf</b></p> |
|--|---|

**Description:**

24 AWG Bonded-Pairs solid bare copper conductors, polyolefin insulation, overall Beldfoil® shield (100% coverage), industrial grade sunlight- and oil-resistant PVC jacket, drain wire, rip cord. Sequential marking at two foot intervals

**SUITABLE APPLICATIONS:**

|                       |  |
|-----------------------|--|
| Suitable Applications | Industrial Ethernet Cable, Harsh Environments, 200MHz Category 5e, Industrial Ethernet, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU Digital Video, RS-422, Noisy Environments, CMX - Outdoor, RJ-45 Compatible |
|-----------------------|--|

**PHYSICAL CHARACTERISTICS:**

**CONDUCTOR:**

|                            |                  |
|----------------------------|------------------|
| Number of Pairs            | 4                |
| Total Number of Conductors | 8                |
| AWG                        | 24               |
| Stranding                  | Solid            |
| Conductor Material         | BC - Bare Copper |

**INSULATION:**

|                                |                 |
|--------------------------------|-----------------|
| Insulation Material            | PO - Polyolefin |
| Nom. Insulation Wall Thickness | .010 in.        |

**Pair Color Code Chart :**

| Number | Color                        | Number | Color                      |
|--------|------------------------------|--------|----------------------------|
| 1      | White/Blue Stripe & Blue     | 3      | White/Green Stripe & Green |
| 2      | White/Orange Stripe & Orange | 4      | White/Brown Stripe & Brown |

**OUTER SHIELD:**

|                                  |                              |
|----------------------------------|------------------------------|
| Outer Shield Material Trade Name | Beldfoil®                    |
| Outer Shield Type                | Tape                         |
| Outer Shield Material            | Aluminum Foil-Polyester Tape |
| Outer Shield % Coverage          | 100 %                        |



**7929A Paired - Category 5e DataTuff® Twisted Pair Cable**

| <b>OUTER SHIELD DRAIN WIRE :</b>           |                    |
|--|--------------------|
| Outer Shield Drain Wire AWG                | 24                 |
| Outer Shield Drain Wire Stranding          | 7x32               |
| Outer Shield Drain Wire Conductor Material | TC - Tinned Copper |

| <b>OUTER JACKET:</b>  |                          |
|-----------------------|--------------------------|
| Outer Jacket Material | PVC - Polyvinyl Chloride |
| Outer Jacket Ripcord  | No                       |

| <b>OVERALL NOMINAL DIAMETER:</b> |          |
|----------------------------------|----------|
| Overall Nominal Diameter         | .265 in. |

| <b>MECHANICAL CHARACTERISTICS:</b> |                 |
|------------------------------------|-----------------|
| Operating Temperature Range        | -40°C To +75°C  |
| Installation Temperature Range     | -25°C To +75°C  |
| Bulk Cable Weight                  | 32 lbs/1000 ft. |
| Max. Recommended Pulling Tension   | 35 lbs.         |
| Min. Bend Radius (Install)         | 0.5 in.         |

**APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:**

| <b>APPLICABLE STANDARDS:</b>          |  |
|---------------------------------------|--|
| NEC/(UL) Specification                | CMR, CMX-Outdoor, UL444                              |
| CEC/C(UL) Specification               | CMR  |
| IEC Specification                     | 11801 Category 5                                     |
| EU RoHS Compliant (Y/N)               | Yes  |
| EU RoHS Compliance Date (mm/dd/yyyy): | 01/01/2004   |
| TIA/EIA Specification                 | 568-B.2 Category 5e                                  |
| Other Specification                   | NEMA WC-63.1 Category 5e, UL verified to Category 5e |

| <b>FLAME TEST:</b> |              |
|--------------------|--------------|
| UL Flame Test      | UL1666 Riser |
| CSA Flame Test     | FT4          |

| <b>SUITABILITY:</b>   |     |
|-----------------------|-----|
| Suitability - Outdoor | Yes |
| Sunlight Resistance   | Yes |
| Oil Resistance        | Yes |

| <b>PLENUM/NON-PLENUM:</b> |       |
|---------------------------|-------|
| Plenum (Y/N)              | N     |
| Plenum Number             | 1533P |
| Non-Plenum Number         | 1533R |



## 7929A Paired - Category 5e DataTuff® Twisted Pair Cable

### ELECTRICAL CHARACTERISTICS:

|   |                       |
|---|-----------------------|
| Nom. Mutual Capacitance @ 1 KHz             | 15 pF/ft              |
| Maximum Capacitance Unbalance (pF/100 m)    | 330 pF/100 m          |
| Nominal Velocity of Propagation             | 70 %                  |
| Maximum Delay (ns/100 m)                    | 538 @ 100MHz ns/100 m |
| Maximum Delay Skew (ns/100m)                | 45 ns/100 m           |
| Maximum Conductor DC Resistance @ 20 Deg. C | 9.38 Ohms/100 m       |
| Maximum DCR Unbalance @ 20 Deg. C           | 3 %                   |
| Max. Operating Voltage - UL                 | 300 V RMS             |

### ELECTRICAL CHARACTERISTICS - PREMISE:

Premise Cable Electricals Table 1 :

| Frequency (MHz) | Max. Attenuation (dB/100 m) | Min. NEXT (dB) | Min. PSNEXT (dB) | Min. ACR (dB) | Min. PSACR (dB) | Min. Return Loss (dB) | Min. Structural Return Loss (dB) |
|-----------------|-----------------------------|----------------|------------------|---------------|-----------------|-----------------------|----------------------------------|
| 1               | 2.0                         | 65.3           | 62.3             | 63.0          | 60.0            | 20.0                  | 23                               |
| 4               | 4.1                         | 56.3           | 53.3             | 51.0          | 49.0            | 23.0                  | 23.0                             |
| 8               | 5.8                         | 51.8           | 48.8             | 46.0          | 43.0            | 24.5                  | 24.5                             |
| 10              | 6.5                         | 50.3           | 47.3             | 43.0          | 41.0            | 25.0                  | 25.0                             |
| 16              | 8.2                         | 47.3           | 44.3             | 39.0          | 36.0            | 25.0                  | 25.0                             |
| 20              | 9.3                         | 45.8           | 42.8             | 36.5          | 33.5            | 25.0                  | 25.0                             |
| 25              | 10.4                        | 44.3           | 41.3             | 33.9          | 30.9            | 24.3                  | 24.3                             |
| 31.25           | 11.7                        | 42.9           | 39.9             | 31.0          | 28.0            | 23.6                  | 23.6                             |
| 62.5            | 17.0                        | 38.4           | 35.4             | 22.0          | 19.0            | 21.5                  | 21.5                             |
| 100             | 22.0                        | 35.3           | 32.3             | 14.0          | 11.0            | 20.1                  | 20.1                             |
| 200             | 32.4                        |                | 27.8             |               | 1.0             |                       | 15.0                             |

Premise Cable Electricals Table 2 :

| Frequency (MHz) | Input (Unfitted) Impedance (Ohms) | Fitted Impedance (Ohms) | Min. ELFEXT (dB) | Min. PSELFEXT (dB) |
|-----------------|-----------------------------------|-------------------------|------------------|--------------------|
| 1               | 100 ± 15                          | 100 ± 15                | 63.8             | 60.8               |
| 4               | 100 ± 15                          | 100 ± 15                | 51.7             | 48.7               |
| 8               | 100 ± 15                          | 100 ± 15                | 45.7             | 42.7               |
| 10              | 100 ± 15                          | 100 ± 15                | 43.8             | 40.8               |
| 16              | 100 ± 15                          | 100 ± 15                | 39.7             | 36.7               |
| 20              | 100 ± 15                          | 100 ± 15                | 37.7             | 34.7               |
| 25              | 100 ± 15                          | 100 ± 15                | 35.8             | 32.8               |
| 31.25           | 100 ± 15                          | 100 ± 15                | 33.9             | 30.9               |
| 62.5            | 100 ± 15                          | 100 ± 15                | 27.8             | 24.8               |
| 100             | 100 ± 15                          | 100 ± 15                | 23.8             | 20.8               |
| 200             | 100 ± 25                          |                         |                  | 14.7               |

### NOTES:



## 7929A Paired - Category 5e DataTuff® Twisted Pair Cable

Notes

US Patent #'s 5, 606, 151; 5, 734, 126. Operating temperatures are subject to length de-rating. Cable passes -40C Cold Bend per UL 1581.

**PUT-UPS AND COLORS:**

| Item          | Description        | Put-Up (ft.) | Ship Weight (lbs.) | Jacket Color | Notes |
|---------------|--------------------|--------------|--------------------|--------------|-------|
| 7929A 0061000 | 4 PR #24 PP FS PVC | 1000         | 37                 | BLUE, LIGHT  | C     |
| 7929A 0101000 | 4 PR #24 PP FS PVC | 1000         | 37                 | BLACK        | C     |
| 7929A 0102000 | 4 PR #24 PP FS PVC | 2000         | 72                 | BLACK        | C     |

C = CRATE REEL PUT-UP.

Revision Number: 7      Revision Date: 09-09-2005

© 2005 Belden Wire & Cable Company  
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden CDT Electronics Division believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.