


PART NUMBER	LENGTH A +/- 1.5mm	COLOR (REF.)	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (Cd/m2)	*RATED LIFE (HRS)
BF20218-24B	218mm	RGB HIGH OUTPUT WHITE 8400°k x = .290 y = .305	1250 @ 0°C	500	5 ± 1	46,000 TYP.	20,000 MIN. 40,000 AVG.
BF20226-24B	226mm		1275 @ 0°C	510			
BF20292-24B	292mm		1650 @ 0°C	660			
BF20325-24B	325mm		1830 @ 0°C	735			

*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

METRIC



THIRD ANGLE
PROJECTION

DIMENSIONS ARE
IN MILLIMETERS

TOLERANCE UNLESS
OTHERWISE SPECIFIED

1 PL +/- 0.2
2 PL +/- 0
ANGLE +/- 0

DRAWN BY
L. WENGSTROM

APPV'D BY DATE
J.K. 4/26/04

SIZE
A

FSCM NO.
55335

DRAWING
NO.

BF 20-24B

REV.
NO.

DESCRIPTION/ECO
NUMBER

APPV'D
DATE

- CAD DRAWING -
MANUAL REVISIONS NOT PERMITTED

SCALE

NONE

RELEASED
DATE

8/14/03

REVISION
DATE

4/26/04

REV.
NO.

A

SHEET
1 OF 1

COMPONENTS CORPORATION

TITLE

**MINIATURE COLD CATHODE
FLUORESCENT LAMP**