


SCALE 1/1



SUGGESTED PANEL CUTOUT





## Specification :

### Material :

1. ST Housing : PBT, UL 94V-0, Ivory color.
2. ST Dust Cover : PVC, Black color.

### Adaptor Type :

- a. ST to ST Simplex Type, Multimode.
- b. Sleeve : Phosphor Bronze.
- c. Operation Temperature : -20°C to +70°C.
- d. Durability : 500 cycles.
- e. Tensile Strength : 10 kgf.
- f. Insertion Loss : <0.3 dB.



GENERAL  
TOLERANCE  
OF DIMENSIONS  
X.XXX ±0.005  
X.XX ±0.05  
X.X ±0.1

|          |             |          |
|----------|-------------|----------|
| DRAWING  | 20.MAY.2005 | Michelle |
| CHECK    | 20.MAY.2005 | YTY      |
| APPROVAL | 20.MAY.2005 | YTY      |

| SCALE | DATE | NAME |
|-------|------|------|
|-------|------|------|

|          |      |    |
|----------|------|----|
| 1/1 (A4) | UNIT | mm |
|----------|------|----|

|                        |                                       |
|------------------------|---------------------------------------|
| DRAWING NO.            | DES: ST to ST Adaptor-Simplex Type MM |
| DRAWING CLASSIFICATION | FIBER ST-ST 1 MM FLANGE               |

**meditronik®**

S SHEET 1 OF 1

