



MBR1635 THRU MBR16100

16.0 AMPS. Schottky Barrier Rectifiers



Voltage Range
35 to 100 Volts
Current
16.0 Amperes



Features

- ✧ Plastic material used carries Underwriters Laboratory Classifications 94V-0
- ✧ Metal silicon junction, majority carrier conduction
- ✧ Low power loss, high efficiency
- ✧ High current capability, low forward voltage drop
- ✧ High surge capability
- ✧ For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- ✧ Guardring for overvoltage protection
- ✧ High temperature soldering guaranteed:
250°C/10 seconds, 0.25" (6.35mm) from case

Mechanical Data

- ✧ Cases: JEDEC TO-220A molded plastic body
- ✧ Terminals: Lead solderable per MIL-STD-750, Method 2026
- ✧ Polarity: As marked
- ✧ Mounting position: Any
- ✧ Mounting torque: 5 in. - lbs. max
- ✧ Weight: 0.08 ounce, 2.24 grams

TO-220A



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

Type Number	MBR 1635	MBR 1645	MBR 1650	MBR 1660	MBR 1690	MBR 16100	Units
Maximum Recurrent Peak Reverse Voltage	35	45	50	60	90	100	V
Maximum RMS Voltage	24	31	35	42	63	70	V
Maximum DC Blocking Voltage	35	45	50	60	90	100	V
Maximum Average Forward Rectified Current at T _c =125°C	16						A
Peak Repetitive Forward Current (Rated V _R , Square Wave, 20KHz) at T _c =125°C	32.0						A
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	150			250			A
Peak Repetitive Reverse Surge Current (Note 1)	1.0		0.5				A
Maximum Instantaneous Forward Voltage at: (Note 2) I _F =16A, T _c =25°C I _F =16A, T _c =125°C	0.63 0.57		0.75 0.65		0.85 0.75		V
Maximum Instantaneous Reverse Current @ T _c =25°C at Rated DC Blocking Voltage (Note 2) @ T _c =125°C	0.2 40.0		1.0 50.0		0.2 -		mA mA
Voltage Rate of Change (Rated V _R)	10,000						V/uS
Maximum Typical Thermal Resistance(Note 3) R _θ JC	1.5						°C/W
Operating Junction Temperature Range T _J	-65 to +150						°C
Storage Temperature Range T _{STG}	-65 to +175						°C

Notes: 1. 2.0us Pulse Width, f=1.0 KHz

2. Pulse Test: 300us Pulse Width, 1% Duty Cycle

3. Thermal Resistance from Junction to Case Per Leg

RATINGS AND CHARACTERISTIC CURVES (MBR1635 THRU MBR16100)

FIG.1- FORWARD CURRENT DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.3- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4- TYPICAL REVERSE CHARACTERISTICS




FIG.5- TYPICAL JUNCTION CAPACITANCE




FIG.6- TYPICAL TRANSIENT THERMAL CHARACTERISTICS

