

# PC827/PC847

※ Lead forming type (I type) and taping reel type (P type) are also available.  
 ※ TÜV (VDE0884) approved type is also available as an option.

## ■ Features

1. Current transfer ratio (CTR:MIN. 50% at  $I_F=5\text{mA}$ ,  $V_{CE}=5\text{V}$ )
2. High isolation voltage between input and output ( $V_{iso}(\text{rms}):5\text{kV}$ )
3. Compact dual-in-line package  
**PC827:** 2-channel type  
**PC847:** 4-channel type
4. Recognized by UL, file No. E64380

## ■ Applications

1. OA equipment
2. Copiers
3. Home appliances


## ■ Absolute Maximum Ratings ( $T_a=25^\circ\text{C}$ )

	Parameter	Symbol	Rating	Unit
Input	Forward current	$I_F$	50	mA
	* <sup>1</sup> Peak forward current	$I_{FM}$	1	A
	Reverse voltage	$V_R$	6	V
	Power dissipation	P	70	mW
Output	Collector-emitter voltage	$V_{CEO}$	35	V
	Emitter-collector voltage	$V_{ECO}$	6	V
	Collector current	$I_C$	50	mA
	Collector power dissipation	$P_C$	150	mW
	Total power dissipation	$P_{tot}$	200	mW
	* <sup>2</sup> Isolation voltage	$V_{iso}(\text{rms})$	5	kV
	Operating temperature	$T_{opr}$	-30 to +100	°C
	Storage temperature	$T_{stg}$	-55 to +125	°C
	* <sup>3</sup> Soldering temperature	$T_{sol}$	260	°C
	*1 Pulse width≤100μs, Duty ratio:0.001			
	*2 40 to 60%RH, AC for 1 minute			
*3 For 10s				

## High Density Mounting Type Photocoupler

### ■ Outline Dimensions

(Unit : mm)



## ■ Electro-optical Characteristics

(T<sub>a</sub>=25°C)

Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Input	Forward voltage	V <sub>F</sub>	I <sub>F</sub> =20mA	—	1.2	V
	Peak forward voltage	V <sub>FM</sub>	I <sub>FM</sub> =0.5V	—	—	V
	Reverse current	I <sub>R</sub>	V <sub>R</sub> =4V	—	—	10 μA
	Terminal capacitance	C <sub>t</sub>	V=0, f=1kHz	—	30	pF
Output	Collector dark current	I <sub>CEO</sub>	V <sub>CE</sub> =20V, I <sub>t</sub> =0	—	—	nA
Transfer characteristics	Collector current	I <sub>C</sub>	I <sub>t</sub> =5mA, V <sub>CE</sub> =5V	2.5	—	30.0 mA
	Collector-emitter saturation voltage	V <sub>CE</sub> (sat)	I <sub>F</sub> =20mA, I <sub>C</sub> =1mA	—	0.1	0.2 V
	Isolation resistance	R <sub>ISO</sub>	DC500V, 40 to 60%RH	5×10 <sup>10</sup>	10 <sup>11</sup>	— Ω
	Floating capacitance	C <sub>f</sub>	V=0, f=1MHz	—	0.6	1.0 pF
	Cut-off frequency	f <sub>c</sub>	V <sub>CE</sub> =5V, I <sub>C</sub> =2mA, R <sub>L</sub> =100Ω, -3dB	—	80	— kHz
	Rise time	t <sub>r</sub>	V <sub>CE</sub> =2V, I <sub>C</sub> =2mA, R <sub>L</sub> =100Ω	—	4	18 μs
	Fall time	t <sub>f</sub>		—	3	18 μs


## ■ Rank Table

(I<sub>F</sub>=5mA, V<sub>CE</sub>=5V, T<sub>a</sub>=25°C)


Model No.	Rank mark	I <sub>C</sub> (mA)
<b>PC8※7AB</b>	A or B	4.0 to 13.0
<b>PC8※7BC</b>	B or C	6.5 to 20.0
<b>PC8※7CD</b>	C or D	10.0 to 30.0
<b>PC8※7AC</b>	A, B or C	4.0 to 20.0
<b>PC8※7BD</b>	B, C or D	6.5 to 30.0
<b>PC8※7AD</b>	A, B, C or D	4.0 to 30.0
<b>PC8※7</b>	A, B, C, D or no mark	2.5 to 30.0







※:2 or 4

**Fig.1 Forward Current vs. Ambient Temperature**




**Fig.2 Collector Power Dissipation vs. Ambient Temperature**




**Fig.3 Peak Forward Current vs. Duty Ratio****Fig.5 Forward Current vs. Forward Voltage****Fig.7 Relative Current Transfer Ratio vs. Ambient Temperature****Fig.4 Current Transfer Ratio vs. Forward Current****Fig.6 Collector Current vs. Collector-emitter Voltage****Fig.8 Collector - emitter Saturation Voltage vs. Ambient Temperature**


**Fig.9 Collector Dark Current vs. Ambient Temperature**




**Fig.11 Response Time vs. Load Resistance**




**Fig.12 Frequency Response**



**Fig.10 Collector-emitter Saturation Voltage vs. Forward Current**



**Test Circuit for Response Time**



**Test Circuit for Frequency Response**

