









CRIMP MALE-FEMALE

	Dimensions A B C	Cable max. mm	To fit cables	Ohm	UG No.	Part No.
Plug straight Stecker gerade Bayonet cap 	29.5 3.1	5	RG 58	50	UG1785/U	IBNC 2010
	29.5 3.1	2.6	RG174/316	50		IBNC 2011
	29.5 3.9	6	RG 59/62	75/93	UG1789/U	IBNC 2012
Bulkhead Jack Gehäusebuchse Bayonet or threaded 	36.3 3.1	5	RG 58	50		IBNC 2020
	36.3 3.9	6	RG 59/62	75/93		IBNC 2021
Jack straight Buchsen gerade Bayonet or threaded 	32.5 3.1	5	RG 58/303	50	UG1794/U	IBNC 2030
	32.5 3.9	6	RG 59/62/302	75/93		IBNC 2031
Plug elbow Winkelstecker Bayonet or threaded cap 	28.0 3.1 27.2	5	RG 58	50		IBNC 2040
	28.0 3.9 27.2	6	RG 59/62	75/93		IBNC 2041

SOLDER MALE-FEMALE

	Dimensions A B	Cable max. mm	To fit cables	Ohm	UG No.	Part No.
Plug straight Stecker gerade Bayonet cap 	28.0 9.5	5	RG 58/223	50	UG88/U	IBNC 1010
	28.0 9.5	6	RG 59	75	UG260/U	IBNC 1011
	28.0 11.0	6	RG 59/62	75/93	UG260B/U	IBNC 1012
Plug elbow Winkelstecker Bayonet cap 	27.0 28.5	5	RG 58/223	50	UG913A/U	IBNC 1030
Jack straight Buchsen gerade Threaded 	29.5 11.0	5	RG 58/223	50	UG89C/U	IBNC 1040
	29.5 11.0	6	RG 59/62	75/93		IBNC 1041
Panel Jack Gehäusebuchse Bayonet 	28.0 9.5	5	RG 58/223	50	UG291/U	IBNC 1050

UG260/L62

Additional technical specifications are available on request. Technical alterations are subject to change without notice.