

PART NUMBER	COLOR 6900°KELVIN	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (Cd/m2)	*RATED LIFE (HRS)	
	x = .325 y = .295	1560 @ 0°C	625 @ 5mA	5.0 TYP.	38,000 TYP.	20,000 MIN. 40,000 AVG.	

^{*} RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC	DIMENS	SIONS ARE						
	+		IVIL II (IO	IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2							
						Ī					
						TITLE	MAINI	IATUDE COLI	CATHODE		
			j T				IVIIIN	MINIATURE COLD CATHOD			
			THIRD ANGLE 2 PL +/- 0		FLUORESCENT LAMP						
			PROJECTION	ANGLE +/- 0			FLOOKLOCKIT LAWIF				
			DRAWN BY	APPV'D B	Y DATE	SIZE	FSCM NO.				
			L. WENGSTROM	J.K.	4/22/04	Α	55335	NO.			
	RELEASED & CANCEL P-0404-13	4/22/04								1	
REV.	DESCRIPTION/ECO	APPV'D	↑ -CADD	Rawing -		SCALE		RELEASED	REVISION	REV.	SHEET
NO.	NUMBER	DATE	MANUAL REVISIONS NOT PERMITTED				NONE	DATE 4/22/04	DATE	NO.	1 _{0F} 1
	HOMBEIT							!	!	!	