


PART NO.	COLOR WHITE	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS) (AVG.)
	x = 0.278 ± 0.01 y = 0.264 ± 0.01	1750 @ 0°C	780	5	42,000 TYP.	40,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC		DIMENSIONS ARE IN MILLIMETERS					
					TOLERANCE UNLESS OTHERWISE SPECIFIED		TITLE			
			THIRD ANGLE PROJECTION		1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		MINIATURE COLD CATHODE FLUORESCENT LAMP			
			DRAWN BY L. WENGSTROM	APPV'D BY L.R.	DATE 8/28/07	SIZE A	FSCM NO. 55335	DRAWING NO.		
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE NONE	RELEASED DATE 11/10/05	REVISION DATE 8/28/07	REV. NO. A	SHEET 1 OF 1
A	START VOLTS TO 2600 & OPER. VOLT TO 1400	8/23/07								
	RELEASED	11/10/05								