

PART NUMBER	- A - LENGTH	COLOR 5000 °k	STARTING CIRCUIT VOLTAGE VS (Vrms) @ 0°C	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
	346±3.0	x = .345±.01	1450	700		36,000±15%	40,000
	397±3.0		1520	725			
	448±3.0		1820	870	0.4		
	499±3.0	y = .360±.01	2100	1000	6± 1		
	550±3.0		2270	1100			
	600±3.0		2340	1125			

\*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC		SIONS ARE						
			( <del>+</del> )	TOLERA	NCE UNLESS						
				1 PL		TITLE	MIN	IATURE COL	D CATHODE		
		THIRD ANGLE PROJECTION		2 PL +/- 0.20 ANGLE +/- 0			FLUORESCENT LAMP				
			DRAWN BY	APPV'D B	Y DATE	SIZE	FSCM NO.				
Α	CHANGE LENGTH & PART NO.		L. WENGSTROM	J.K.	11/18/04	Α	55335	NO.			
	RELEASE & CANCEL P-0410-05	11/17/04	CADD	DAMING		SCALE	33333	RELEASED	REVISION	REV. A	SHEET
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			NONE	DATE 11/17/04	DATE 11/18/04	NO. A	1 <sub>OF</sub> 1	