



PART NO. (REFERENCE)	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms) @ 0°C	OPERATING LAMP VOLTAGE VL (Vrms) @ 25°C	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS) MINIMUM
	x = .325 y = .295	1715	730	5 ± 1	30,000 ± 3000	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OFTHE INITIAL RATING.

			METRIC		DIMENSIONS ARE IN MILLIMETERS					
					TOLERANCE UNLESS OTHERWISE SPECIFIED		TITLE			
			THIRD ANGLE PROJECTION		1 PL +/- 0.2 2 PL +/- 0.20 ANGLE +/- 0		MINIATURE COLD CATHODE FLUORESCENT LAMP			
			DRAWN BY L. WENGSTROM	APPV'D BY L.R.	DATE 8/5/09	SIZE A	FSCM NO. 55335	DRAWING NO.		
A	RATED LIFE HRS MINIMUM HEADING & 20,000	8/5/09	- CAD DRAWING -			SCALE NONE		RELEASED DATE 1/29/03	REVISION DATE 8/5/09	REV. NO. A
RELEASED & CANCEL P-0210-08 & BF26349-28B			MANUAL REVISIONS NOT PERMITTED							SHEET 1 OF 1
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE								