



PART NUMBER	COLOR LCD HIGH OUTPUT WHITE 5600°K (RGB)	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
	x = 0.337 ± .03 y = 0.368 ± .03	800	260	5	9,500 ± 10%	20,000

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			<b>METRIC</b>  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0		TITLE <b>SINGLE LEAD TIPLESS MINIATURE FLUORESCENT LAMP</b>				
DRAWN BY L. WENGSTROM			APPV'D BY L. R.		DATE 7/5/06		SIZE <b>A</b>	FSCM NO. <b>55335</b>	DRAWING NO.		
ADD x & y COORDINATED RELEASED TO CAD			7/5/06 9/17/02		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE	RELEASED DATE 9/17/02	REVISION DATE 7/5/06	REV. NO. <b>A</b>	SHEET 1 OF 1