



PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS) TYPICAL
BF22258-25B	LCD HIGH OUTPUT WHITE 9700°k RGB	1600 @ 0°C	535	5 ± 1	38,000 ±10%	50,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

METRIC THIRD ANGLE PROJECTION			DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0			TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP					
F RATED LIFE HRS. TYPICAL & 20,000 TO 50,000 8/19/09 E ADD MINIMUM TO RATED LIFE HRS. 7/16/09 D CHANGE ON ELECT. CHART 4/16/09 C CHANGE ON CIRCUIT & LAMP VOLTAGE 7/19/04 B CHANGE ON OUTPUT RGB 11/11/02 A NEW CHART 6/5/01 RELEASED 6/4/01			DRAWN BY L. WENGSTROM		APPV'D BY DATE L.R. 8/19/09		SIZE A	FSCM NO. 55335	DRAWING NO. BF22258-25B		
REV. NO. DESCRIPTION/ECO NUMBER APPV'D DATE			- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED				SCALE NONE	RELEASED DATE 6/4/01	REVISION DATE 8/19/09	REV. NO. F	SHEET 1 OF 1