

PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)	
BF3222-24B	LCD HIGH OUTPUT WHITE 7400°k RGB	1100 @ 0°C	440	5 ± 1	28,000 ± 10%	20,000	

^{*} RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC	DIMENSIONS ARE IN MILLIMETERS						
			(()-(-)-	TOLERANCE UNLESS OTHERWISE SPECIFIED	TITLE					
	1	1		1 PL +/- 0		MIN	IATURE COLI	CATHODE		
			THIRD ANGLE PROJECTION	2 PL +/- 0 ANGLE +/- 0		FLU	ORESCENT L	AMP		
			DRAWN BY	APPV'D BY DATE	SIZE	FSCM NO.	DRAWING			
			L. WENGSTROM	FD 8/20/02	Α	55335	NO. BF	3222-24B		
	RELEASED	8/20/02	- CAD D	RAWING -	SCALE		RELEASED	REVISION	REV.	SHEET
REV NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE		NS NOT PERMITTED		NONE	DATE 8/20/02	DATE	NO.	1 of 1