


PART NUMBER	LENGTH A +/- 2mm	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF6262-30A	262mm	DAYLIGHT WHITE	850	350	5 ± 1	3,000	20,000

*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0						
			DRAWN BY L. WENGSTROM		APPV'D BY JK		DATE 11/27/00		TITLE DUAL LEAD TIP TYPE DAYLIGHT WHITE MINIATURE FLUORESCENT LAMP		
RELEASED			11/27/00		SIZE A		FSCM NO. 55335		DRAWING NO.		
REV. NO.			DESCRIPTION/ECO NUMBER		APPV'D DATE		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE		
							RELEASED DATE 11/27/00		REVISION DATE		
							REV. NO.		SHEET 1 OF 1		