


Palm grip B 6

1/290 2002



The palm grip B 6 is an actuating element for our multi-axis and single axis controller. It can also be used as an actuating element with hydraulic drives. Pushbuttons, rocker switches, e.t.c., can also be fitted to suit appropriate requirements. These devices have micro changeover contacts.

The palm grip has a highly flexible cable 4 (8) x 0,25 mm² x 450 mm long.

The mounting piece for the drive rod can be supplied with a tapped hole M 8 or M 10 (standard = M 10).

The palm grip B 6 is made of PPO plastic and is black in color.

2 A 250 V AC 15 / 3 A 24 V DC 13 0,5 A 250 V AC 15 / 1,5 A 24 V DC 13 Contact complement

Permissible ambient temperature

Operating -40°C to +60°C Storage -50°C to +80°C Storage

Climate resistance Damp heat constant Damp heat cyclic Degree of protection front

DIN IEC 68 part 2-3 DIN IEC 68 part 2-30 IP 54 IEC 529 DIN 40050

2			Contact-	т	Weight	Price	
Pos.			complement	Drawing No.	Туре	gramm	EUR
1	with built in Lever switch side 0-tast		1 change over contacts 0,5A 250V AC 15	KBAD/	B 6 K	120	
2 3 4	Lever switch side 0-tast with Rocker switch top tast-0-tast with Rocker switch top tast-0-rest T - O - T T - O - R T - O - R T - O - R		3 change over contacts 0,5A 250V AC 15	KBAD/	B 6 KW	130	
5	Lever switch side 0-tast with push button top		2 change over contacts 0,5A 250V AC 15	KBAD/	B 6 KD	130	
21 22	Cable 4 res. 8 x 0,25 mm² wired included Pos. 1-5 Additional price per metre Additional price per metre	cable 4-pole					