



Electrical Data		
Nominal resistance	1/5/10	kOhm
Resistance tolerance	±20	%
Independent linearity	±2	% of meas. range
Electrical angle	270	°
Temperature coefficient of the voltage divider	50	ppm/°C
Recommended wiper current	max. 1	µA
Max. wiper current in case of malfunction	10	mA
Power rating P	max. 0.5	W/40°C
Min. life (electrical)	1 Mio.	cycles
Mechanical Data		
Mechanical range	300	°
Torque	max. 1	Ncm
Min. life (mechanical)	500'000	cycles
Operating temperature	-25 ... +125	°C
Storage temperature	-40 ... +125	°C
Protection class	IP50	
Standards		
Insulating resistance (500 VDC, 1bar, 2s)	10	GOhm
Dielectric strength (VAC, 50Hz, 1min, 1bar)	1.5	kV
Vibration (Amax = 0.75mm, f = 30 ... 2000 Hz)	10	g
Shock (half sine pulse, 7 ms)	50	g

PL290

Applications

- Electrical servo drive
- Rehabilitation equipment

Features

- Small dimensions
- 0.5 Mio. cycles
- Very good resolution, better 0,1°
- Linearity ±2 %

Options

- Custom shafts design
- Custom bushing design
- Other electrical angles between 20° und 270°
- Continuous rotation

Subject to change
without notice
State: 27-Oct-2005

Contelec AG
Portstrasse 38
CH-2503 Biel/Bienne
Phone +41 (0)32 3665600
Telefax +41 (0)32 3665604
sales@contelec.ch

CONTELEC