

Fully Sealed Container Cermet Potentiometers Submarine Applications



FEATURES

- High power rating 1.5 W at 70 °C
- Stainless steel shaft and bushing to endure sea salt water immersion
- Fully sealed IP68 on panel
- Tight temperature coefficient (± 75 ppm/°C typical)
- Compliant to RoHS Directive 2002/95/EC



P13SM is designed for applications which need to set electrical parameters with an immersed potentiometer in deep water conditions up to 30 m (100 feet).

DIMENSIONS in millimeters (inches) ± 0.5 mm (± 0.02 ")

P13SM N

P13SM B

Note
(1) CAUTION: Ø 1.5 of panel cut out must not be fully through hole.

P13SM

Fully Sealed Container Cermet Potentiometers Submarine Applications

ELECTRICAL SPECIFICATIONS					
Resistive Element	Cermet				
Electrical Travel	$270^\circ \pm 10^\circ$				
Resistance Range	<table style="width: 100%; border: none;"> <tr> <td style="text-align: center; width: 30%;">Linear Taper</td> <td style="text-align: center;">22 Ω to 10 MΩ</td> </tr> <tr> <td style="text-align: center;">Logarithmic Taper</td> <td style="text-align: center;">1 kΩ to 2.2 MΩ</td> </tr> </table>	Linear Taper	22 Ω to 10 M Ω	Logarithmic Taper	1 k Ω to 2.2 M Ω
Linear Taper	22 Ω to 10 M Ω				
Logarithmic Taper	1 k Ω to 2.2 M Ω				
Standard Series E3	1, 2.2, 4.7 and on request 1, 2, 5				
Tolerance	<table style="width: 100%; border: none;"> <tr> <td style="text-align: center; width: 30%;">Standard</td> <td style="text-align: center;">$\pm 20\%$</td> </tr> <tr> <td style="text-align: center;">On Request</td> <td style="text-align: center;">$\pm 10\%$ to $\pm 5\%$</td> </tr> </table>	Standard	$\pm 20\%$	On Request	$\pm 10\%$ to $\pm 5\%$
Standard	$\pm 20\%$				
On Request	$\pm 10\%$ to $\pm 5\%$				
Taper					
Circuit Diagram					
Power Rating	<table style="width: 100%; border: none;"> <tr> <td style="width: 30%;">Linear</td> <td>1.5 W at 70 $^\circ\text{C}$</td> </tr> <tr> <td>Logarithmic</td> <td>0.75 W at 70 $^\circ\text{C}$</td> </tr> </table>	Linear	1.5 W at 70 $^\circ\text{C}$	Logarithmic	0.75 W at 70 $^\circ\text{C}$
Linear	1.5 W at 70 $^\circ\text{C}$				
Logarithmic	0.75 W at 70 $^\circ\text{C}$				
Temperature Coefficient (Typical)	<table style="width: 100%; border: none;"> <tr> <td style="width: 30%;"></td> <td style="text-align: center;">± 150 ppm/$^\circ\text{C}$</td> </tr> <tr> <td></td> <td style="text-align: center;">For values $\geq 100 \Omega$ and in temperature range + 20 $^\circ\text{C}$ to + 70 $^\circ\text{C}$, the typical temperature coefficient is ± 75 ppm/$^\circ\text{C}$</td> </tr> </table>		± 150 ppm/ $^\circ\text{C}$		For values $\geq 100 \Omega$ and in temperature range + 20 $^\circ\text{C}$ to + 70 $^\circ\text{C}$, the typical temperature coefficient is ± 75 ppm/ $^\circ\text{C}$
	± 150 ppm/ $^\circ\text{C}$				
	For values $\geq 100 \Omega$ and in temperature range + 20 $^\circ\text{C}$ to + 70 $^\circ\text{C}$, the typical temperature coefficient is ± 75 ppm/ $^\circ\text{C}$				
Limiting Element Voltage (Linear Law)	350 V				
Contact Resistance Variation	3 % Rn or 3 Ω				
End Resistance (Typical)	1 Ω				
Dielectric Strength (RMS)	2000 V				
Insulation Resistance (300 V _{DC})	10 ⁶ M Ω				
Independent Linearity (Typical)	$\pm 5\%$				

Fully Sealed Container Cermet Potentiometers
Submarine Applications

STANDARD RESISTANCE ELEMENT DATA							
STANDARD RESISTANCE VALUES	LINEAR TAPER			LOGS TAPER			TYPICAL TCR - 55 °C + 125 °C
	MAX. POWER AT 70 °C	MAX. WORKING VOLTAGE	MAX. CUR. THROUGH WIPER	MAX. POWER AT 70 °C	MAX. WORKING VOLTAGE	MAX. CUR. THROUGH WIPER	
Ω	W	V	mA	W	V	mA	ppm/°C
22	1.5	5.74	261				± 150
47	1.5	8.4	177				
100	1.5	12.2	122				
220	1.5	18.2	82.6				
470	1.5	26.5	56.5				
1K	1.5	38.7	38.7	0.75	27	27	
2.2K	1.5	57.5	26.1	0.75	40	18	
4.7K	1.5	84	17.9	0.75	59	12	
10K	1.5	122.5	12.2	0.75	87	8.7	
22K	1.5	182	8.26	0.75	128	5.8	
47K	1.5	265	5.65	0.75	187	3.9	
100K	1.22	350	3.5	0.75	273	2.7	
220K	0.56	350	1.6	0.56	350	1.6	
470K	0.26	350	0.74	0.26	350	0.74	
1M	0.12	350	0.35	0.12	350	0.35	
2.2M	0.05	350	0.16	0.05	350	0.16	
4.7M	0.026	350	0.074				
10M	0.012	350	0.035				

MECHANICAL SPECIFICATIONS			
Mechanical Travel	Style B	300° ± 5°	
	Style N	310° ± 5°	
Operating Torque (Typical)		2 Ncm max.	2.85 oz. inch max.
End Stop Torque	Style B	35 Ncm max.	3.1 lb inch max.
	Style N	80 Ncm max.	7.1 lb inch max.
Tightening Torque of Mounting Nut	Style B	80 Ncm min., 150 Ncm max.	7 lb inch min., 13.3 lb inch max.
	Style N	80 Ncm min., 250 Ncm max.	7 lb inch min., 22.1 lb inch max.
Unit Weight		8 g to 27 g max.	0.3 oz. to 1 oz.
Terminals		e3: Pure Sn	

ENVIRONMENTAL SPECIFICATIONS	
Temperature Range	- 55 °C to 125 °C
Climatic Category	55/125/56
Sealing	Fully sealed - Container IP68
Panel sealing	Immersion at 30 m (100 feet) in sea salt water or clear water

P13SM

Fully Sealed Container Cermet Potentiometers Submarine Applications

OPTIONS

Special Feature Command Shaft

Length is measured from the mounting surface to the free end of the shaft. The screwdriver slot is aligned with the wiper within $\pm 10^\circ$. Special shafts are available, in accordance to drawings supplied by customers. We recommend that customers should not machine tool shafts, in order to avoid damage. Bending or torsion of terminals should also be avoided.

MARKING

Printed:

- Vishay trademark
- Part number (including ohmic value code, tolerance code and resistance law)
- Manufacturing date
- Marking of terminals a

PACKAGING

In box

Packaging quantity depending on shafts:

- Box of 8 pieces for shaft FR (code BO8)
- Box of 10 pieces for shaft FG or FL (code BO10)
- Box of 15 pieces for shaft BJ (code BO15)
- Box of 25 pieces for shaft BB (code BO25)

PERFORMANCE

TESTS	CONDITIONS	TYPICAL VALUES AND DRIFTS		
		$\Delta R_T/R_T$ (%)	$\Delta R_{1-2}/R_{1-2}$ (%)	OTHER
Electrical Endurance	1000 h at rated power 90'/30' - ambient temp. 70 °C	± 1 %	-	Contact res. variation: < 3 % Rn
Climatic Sequence	Phase A dry heat 125 °C Phase B damp heat Phase C cold - 55 °C Phase D damp heat 5 cycles	± 0.5 %	± 1 %	-
Damp Heat, Steady State	56 days 40 °C 93 % HR	± 0.5 %	± 1 %	Dielectric strength: 1000 V Insulation resistance: > 10 ⁴ MΩ
Change of Temperature	5 cycles - 55 °C at + 125 °C	± 0.5 %	-	-
Mechanical Endurance	25 000 cycles	± 3 %	-	Contact res. variation: < 2 % Rn
Shock	50 g's at 11 ms 3 successive shocks in 3 directions	± 0.1 %	± 0.2 %	-
Vibration	10 Hz to 55 Hz 0.75 mm or 10 g's during 6 h	± 0.1 %	-	$\Delta V_{1-2}/V_{1-3} < \pm 0.2$ %

Fully Sealed Container Cermet Potentiometers Submarine Applications

ORDERING INFORMATION (Part Number)																	
P	1	3	S	M	N	F	L	S	1	0	3	M	A	E			
MODEL	BUSHING			SHAFT			SHAFT STYLE	OHMIC VALUE	TOLERANCE	TAPER	SPECIAL						
P13SM	∅	L	Shaft ∅		∅	L	S = Slotted On request: R = Round F = Flat D = Custom	Linear law from 22 Ω to 10 MΩ Logarithmic law from 1 kΩ to 2.2. MΩ 103 = 10 kΩ	M = 20 % On request: K = 10 % J = 5 %	A = Linear L = Clockwise logarithmic F = Inverse clockwise logarithmic	E = Locating peg or special code given by Vishay						
	N	10	10.3	6	BB	3.17	12.7										
	B	6.35	9.52	3.17	BJ	3.17	22.2										
					FG	6	16										
					FL	6	25										
					FR	6	50										
					AP	Custom											

PART NUMBER DESCRIPTION (for information only)												
P13SM	N	E	FL	S	10K	20 %	A		BO10			e3
MODEL	BUSHING	SPECIAL	SHAFT	SHAFT STYL	VALUE	TOLERANCE	TAPER	SPECIAL	PACKAGING	SHAFT	SPECIAL	LEAD (Pb)-FREE