

QNAP TS-1253-RP 12-BAY

Processor	Quad-core Intel® Celeron® 2.0GHz (up to 2.42GHz) Installed: 4GB DDR3L SDRAM (1 x 4GB) Slots: 2 SODIMM (Max: 8GB)
Memory	NOTE: 1. When installing two memory modules, please ensure that they are the same size and ideally use the same type of RAM for both memory slots. 2. For the information of RAM module installation and compatible NAS models, please refer to the QNAP RAM Module Installation Guide
Flash memory	512MB 12 x 3.5" or 2.5" SATA 6Gb/s, SATA 3Gb/s hard drive or SSD
Internal drive	NOTE: 1. The system is shipped without HDD. 2. HDD compatibility list
Drive tray	12 Hot-swappable and lockable trays
Network interface	4 RJ45 Gigabit Ethernet ports
Ports	4 USB 3.0 1 HDMI 1 console (system maintenance)
LED indicators	Status, LAN, USB, HDD 1-12
Buttons	Power, reset
Alarm buzzer	System warning
Form factor	2U, rack mountable
Dimensions	89 (H) x 482 (W) x 534 (D) mm 3.5 (H) x 18.98 (W) x 21.02 (D) inch
Weight	Net weight: 16.14 kg (35.58 lbs.) Gross weight: 18.98 kg (41.84 lbs.)
Power consumption (W)	HDD standby: 47.85W In operation: 126.59W (with 12 x 2TB HDD installed)
Sound Level*	Sound pressure (LpAm) :37.5 dB(A)
Temperature	0-40°C
Humidity	0~95% R.H.
Power supply	Input: 100-240V AC, 50/60Hz; Output: Redundant 250W
Fan	2 x 70mm, 12V DC