

QNAP TS-1280U-E3 12-BAY

| | |
|-------------------|---|
| Model Name | TS-EC1280U-E3-4GE-R2 TS-EC1280U-i3-4GE-R2 TS-EC1280U-i3-8G-R2 |
| CPU | TS-EC1280U-E3-4GE-R2: Intel® Xeon® E3-1246 v3 Quad-core processor TS-EC1280U-i3-4GE-R2: Intel® Core i3-4150 processor TS-EC1280U-i3-8G-R2: Intel® Core i3-4150 processor Total memory slots: 4 TS-EC1280U-E3-4GE-R2/ TS-EC1280U-i3-4GE-R2: |

System memory: 4 GB DDR3 ECC RAM
Memory module pre-installed: 2 GB x2
Memory expandable up to: 32 GB (8GB x4)

| | |
|---------------|--|
| Memory | TS-EC1280U-i3-8G-R2: System memory: 8 GB DDR3 non-ECC RAM Memory module pre-installed: 4 GB x2 Memory expandable up to: 32 GB (8GB x4) |
|---------------|--|

Note:

1. When upgrading RAM to more than 28GB, the original 4GB RAM modules must be removed.
2. For the information of RAM module installation and compatible NAS models, please refer to the [QNAP RAM Module Installation Guide](#)

Flash Memory 512MB DOM

Two mSATA port on board for read caching

Internal Cache Port Note: The standard system is shipped without mSATA flash. For the optional mSATA flash, please visit <http://shop.qnap.com/>

12 x 3.5-inch SATA 6Gbps/3Gbps hard drive or 2.5-inch SATA, 6Gbps/3Gbps hard drive SSD hard drive

NOTE:

Hard Drive

1. The standard system is shipped without hard drives.
2. For the hard drive compatibility list, please visit [Compatibility list](#)

Hard Drive Tray 12 x hot-swappable and lockable tray

LAN Port Built-in 2 x 10 GbE SFP+ ports (LAN-10G2SF-MLX) and 4 x GbE ports
40GbE is optional

Note:

1. For the optional network card compatibility list, please visit [Compatibility list of Expansion Card](#)
2. For the information of network card installation, please refer to chapter 6 in the [Turbo NAS Hardware Manual](#).

| | |
|------------------------------|---|
| LED Indicators | Status, 10 GbE, LAN, eSATA, storage expansion port status |
| USB | 4x USB 3.0 port (rear) 4x USB 2.0 port (rear) |
| Buttons | Support USB printer, pen drive, USB hub, and USB UPS etc. System: Power button and reset button |
| Alarm Buzzer | System warning |
| Form Factor | 2U, Rackmount |
| Dimensions | 88(H) x 442.5(W) x 530.5(D) mm 3.46(H) x 17.42(W) x 20.89(D) inch |
| Weight | Net weight (NAS only) : 14.18 kg/ 31.26 lb Gross weight (with packing and accessories) : 21.41 kg/ 47.20 lb |
| Power Consumption (W) | Sleep mode: 80.41 In Operation: 166.58 W (with 12 x 1TB hard drive installed) |
| Sound Level* | Sound pressure (LpAm) :55.3 dB(A) |
| Temperature | 0-40°C |
| Relative Humidity | 5~95% non-condensing, wet bulb: 27°C. |
| Power Supply | Redundant power: Input: 47-63 Hz; 100-127V~/ 8A; 200-240V/ 4A Output: 400W 2 (Right slot: 1* PCIe Gen3 x8; Left slot: 1* PCIe Gen3 x4) |
| PCIe Slot | Note: The PCIe Gen3 x8 slot is occupied by a 10GbE network adapter. |
| Fan | 4 x 6 cm smart cooling fan |