



VM-8H

1:8 HDMI Distribution Amplifier



The **VM-8HDMI** is a distribution amplifier for HDMI signals. It reclocks and equalizes the signal and distributes it to eight identical outputs.

FEATURES

- MaxData Rate - 1.65Gbps.
- HDTV Compatible.
- HDCP Compliant.
- HDMI Support - Deep Color, x.v.Color™, Lip Sync, CEC.
- 3D Pass-Through.
- Enhanced EDID (Extended Display identification Data) - The unit can store and recall a default EDID setting in non-volatile memory from the output allowing convenient and reliable connection to the source.
- Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances.
- Active Output LED Indicators.
- Worldwide Power Supply - 100-264V AC
- Standard 19" Rack Mount Size - 1U



VM-8H

TECHNICAL SPECIFICATIONS

INPUT:	HDMI Connector
OUTPUTS:	8 HDMI Connectors
BANDWIDTH:	Supports up to 1.65Gbps per graphic channel
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI 1.0 and HDCP
CONTROLS:	SELECT and READ buttons for selecting and storing EDID information
INDICATOR LEDs:	OUTPUT STATUS 1 to 8
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
POWER SOURCE:	100-264 VAC, 50/60Hz 25VA
DIMENSIONS:	19-inch (W), 7-inch (D), 1U (H)
WEIGHT:	3.5kg. (7.7lbs.) approx.
ACCESSORIES:	Power cord

