



VS-66HDCP

6x6 DVI Matrix Switcher



The VS-66HDCP is a high-performance matrix switcher for DVI signals. The unit reclocks and equalizes the signal and can route any or all inputs to any or all outputs simultaneously.

FEATURES

- **Max Data Rate** - 1.65Gbps.HDTV Compatible.HDCP Compliant.Kramer re-Klocking & Equalization Technology - Rebuilds the digital signal integrity to travel longer distances.Smart EDID (Extended Display Identification Data) Recall - The unit can store and recall a default EDID setting in non-volatile memory from the output, allowing convenient and reliable connection to the source.Flexible Control Options - Front panel, IR Remote, RS-232 (K Router™ Windows®-based software is included) & Ethernet (Windows®-based Ethernet Configuration Manager & Virtual Serial Port Manager is included).Output Disconnect - Each output.Front Panel Lockout.Memory Locations - Stores multiple switches as presets to be recalled and executed as needed.Worldwide Power Supply - 100-240V AC.Standard 19" Rack Mount Size - 1U. Rack "ears" included.
- **INPUTS:** - 6 DVI connectors
- **OUTPUTS:** - 6 DVI connectors
- **Input/Output** - DVI-D signals (on DVI-I connectors).
- **HDMI Support** - HDMI Compressed Audio Channels.
- **BANDWIDTH:** - Supports up to 1.65Gbps bandwidth per graphic channel
- **Smart EDID (Extended Display Identification Data)** - Dedicated memory for each input captures an EDID setting from a device connected to the output and stores it in non-volatile memory. The user can recall this setting or a factory default EDID.
- **STANDARDS COMPLIANCE:** - Supports DVI 1.1 and HDCP
- **MAX RESOLUTION:** - Up to UXGA; 1080p, 1920 x 1200
- **POWER SOURCE:** - 100-240V AC; 50/60Hz, 32VA
- **CONTROLS:** - Front panel buttons, infrared remote control transmitter, RS-232, Ethernet
- **DIMENSIONS:** - 19" x 7" x 1U W, D, H
- **WEIGHT:** - 2.5kg (5.5lbs) approx.



VS-66HDCP

TECHNICAL SPECIFICATIONS

ACCESSORIES:	Power cord, IR transmitter
OPTIONS:	Kramer cables
BANDWIDTH:	Supports up to 1.65Gbps bandwidth per graphic channel.
COMPLIANCE WITH STANDARDS:	Supports DVI and HDCP.
MAX RESOLUTION:	Up to UXGA, 1080p, 1920x1200.
CONTROLS:	Front panel buttons, infra-red remote control transmitter, RS-232, Ethernet.
INDICATORS:	6-character display on the front panel.
POWER SOURCE:	100-240V AC; 50/60Hz, 32VA.
DIMENSIONS:	19" x 7" x 1U W, D, H, rack mountable.
WEIGHT:	2.5kg (5.5lbs) approx.
ACCESSORIES:	Power cord, IR transmitter.
OPTIONS:	Kramer cables.

